

## **NBPMPNN015PAUNV**

#### **NBPMPNN015PAUNV Information**

Part Number NBPMPNN015PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRES 15PSI ABSO 12V SMT

Package 4-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **NBPMPNN015PAUNV Specifications**

Manufacturer Part NumberNBPMPNN015PAUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SMD, J-Lead, Top PortSeriesNBPPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-Report errors?		
Category Sensors, Transducers Package Package Pressure Sensors, Transducers Package Pressure Type Pressure Type Absolute Operating Pressure Output Type Wheatstone Bridge Output Om V ~ 75 mV (5V) Accuracy  Voltage - Supply 1.8 V ~ 12 V  Port Size Port Style No Port Features - Termination Style Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case Sunsors, Transducers Pressure Sensors, Transducers Port Sup Port NBP Port Size 1.5 PSI (103.42 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package	Manufacturer Part Number	NBPMPNN015PAUNV
Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 75 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Sure Surface Mount Surface Mount -10 Port Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         4-SMD, J-Lead, Top Port           Series         NBP           Pressure Type         Absolute           Operating Pressure         15 PSI (103.42 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 75 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.8 V ~ 12 V           Port Size         -           Port Style         No Port           Features         -           Termination Style         Surface Mount           Maximum Pressure         30 PSI (206.84 kPa)           Operating Temperature         -40°C ~ 125°C           Package / Case         4-SMD, J-Lead, Top Port           Supplier Device Package         -	Category	Sensors, Transducers
SeriesNBPPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Package	4-SMD, J-Lead, Top Port
Operating Pressure  15 PSI (103.42 kPa)  Output Type  Wheatstone Bridge  Output  0 mV ~ 75 mV (5V)  Accuracy  ±0.25%  Voltage - Supply  1.8 V ~ 12 V  Port Size  - Port Style  No Port  Features  - Termination Style  Surface Mount  Maximum Pressure  30 PSI (206.84 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Supplier Device Package  -  15 PSI (103.42 kPa)  Wheatstone Bridge  Wheatstone Bridge  0 mV ~ 75 mV (5V)  **Device Package**  15 PSI (103.42 kPa)  0 mV ~ 75 mV (5V)  **Device Package**  18 V ~ 12 V  **Device Package**	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Pressure Type	Absolute
Output $0 \text{ mV} \sim 75 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure $30 \text{ PSI} (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-SMD}$ , J-Lead, Top Port Supplier Device Package $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Pressure	15 PSI (103.42 kPa)
Accuracy ±0.25%  Voltage - Supply 1.8 V ~ 12 V  Port Size - Port Style No Port  Features - Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply  1.8 V ~ 12 V  Port Size  - Port Style No Port Features - Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Output	$0 \text{ mV} \sim 75 \text{ mV} (5\text{V})$
Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style No Port  Features -  Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Port Size	-
Termination Style  Surface Mount  30 PSI (206.84 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  4-SMD, J-Lead, Top Port  Supplier Device Package  -	Port Style	No Port
Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C  Package / Case 4-SMD, J-Lead, Top Port  Supplier Device Package -	Termination Style	Surface Mount
Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-SMD, J-Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

### **NBPMPNN015PAUNV Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **NBPMPNN015PAUNV Payment Methods**



















### **NBPMPNN015PAUNV Shipping Methods**













If you have any question about NBPMPNN015PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com