

NBPMPNS060PAUNV

NBPMPNS060PAUNV Information



For Reference Only

Part Number NBPMPNS060PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 60PSI ABSO 12V SMT

Package 4-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPMPNS060PAUNV Specifications

Manufacturer Part Number NBPMPNS060PAUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Absolute Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package - Report errors?		
Category Sensors, Transducers Package Package Pressure Sensors, Transducers Package Pressure Sensors, Transducers Package Pressure Type NBP Pressure Type Absolute Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Manufacturer Part Number	NBPMPNS060PAUNV
Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Absolute Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Sure Surface Mount Surface Mount - Surplier Device Package - Surply In Surface Mount - Surplier Device Package - Surface Mount - Surplier Device Package - Surplier Device	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-SMD, J-Lead, Top PortSeriesNBPPressure TypeAbsoluteOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Category	Sensors, Transducers
SeriesNBPPressure TypeAbsoluteOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Package	4-SMD, J-Lead, Top Port
Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Pressure Type	Absolute
Output $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $-$ Port Style No Port Features $-$ Termination Style Surface Mount Maximum Pressure $120 \text{ PSI (827.37 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-SMD, J-Lead, Top Port}$ Supplier Device Package $-$	Operating Pressure	60 PSI (413.69 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-SMD, J-Lead, Top Port}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Output	$0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$
Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Size	-
Termination Style Surface Mount 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Style	No Port
Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Termination Style	Surface Mount
Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Maximum Pressure	120 PSI (827.37 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-SMD, J-Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPMPNS060PAUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPMPNS060PAUNV Payment Methods



















NBPMPNS060PAUNV Shipping Methods













If you have any question about NBPMPNS060PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com