

NBPMPNS160MGUNV

NBPMPNS160MGUNV Information

Part Number NBPMPNS160MGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 4-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPMPNS160MGUNV Specifications

Manufacturer Part NumberNBPMPNS160MGUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SMD, J-Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure2.32 PSI (16 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-Report errors?		
Category Sensors, Transducers Package Package Pressure Sensors, Transducers Package Pressure Type Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output Om V ~ 75.5 mV (5V) Accuracy Voltage - Supply 1.8 V ~ 12 V Port Size Port Style No Port Features Termination Style Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature 4-0°C ~ 125°C Package / Case Sunsors, Transducers Pressure Sensors, Transducers Port Sup Port Port Sup Port Port Sup Port Package / Case Package Pa	Manufacturer Part Number	NBPMPNS160MGUNV
Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output Output 0 mV ~ 75.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Sure 1.8 MBP NBP Vented Gauge Vented	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-SMD, J-Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure2.32 PSI (16 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Category	Sensors, Transducers
SeriesNBPPressure TypeVented GaugeOperating Pressure2.32 PSI (16 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 2.32 PSI (16 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 75.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package	Package	4-SMD, J-Lead, Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 75.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 2.32 PSI (16 kPa) Wheatstone Bridge No Wheatstone Bridge 10 mV ~ 75.5 mV (5V) - **ONE OF TO	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 75.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 75.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure $12.33 \text{ PSI } (85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{SMD, J-Lead, Top Port}$ Supplier Device Package-	Operating Pressure	2.32 PSI (16 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StyleSurface MountMaximum Pressure $12.33 \text{ PSI (85 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{SMD, J-Lead, Top Port}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Output	$0 \text{ mV} \sim 75.5 \text{ mV} (5\text{V})$
Port Size - No Port Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style No Port Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Size	-
Termination Style Surface Mount 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Style	No Port
Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Termination Style	Surface Mount
Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Maximum Pressure	12.33 PSI (85 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-SMD, J-Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPMPNS160MGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPMPNS160MGUNV Payment Methods



















NBPMPNS160MGUNV Shipping Methods













If you have any question about NBPMPNS160MGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com