

NCP160BMX275TBG

NCP160BMX275TBG Information

Heisener.com

Part NumberNCP160BMX275TBGManufacturerON SemiconductorCategoryIntegrated Circuits (ICs)

PMIC - Voltage Regulators - Linear

Description IC REG LINEAR 250MA

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NCP160BMX275TBG Specifications

Manufacturer Part Number NCP160BMX275TBG Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Package - Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.75V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 250mA Current - Quiescent (Iq) - Current - Supply (Max) 23µA PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Enable Protection Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package - Report errors?	•	
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package - Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.75V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 250mA Current - Quiescent (Iq) - Current - Supply (Max) 23µA PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Enable Protection Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	NCP160BMX275TBG
Package - Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.75V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 250mA Current - Quiescent (Iq) - Current - Supply (Max) 23μA PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Enable Protection Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer	ON Semiconductor
Package - Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.75V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 250mA Current - Quiescent (Iq) - Current - Supply (Max) 23μA PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
Series-Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.75VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-		PMIC - Voltage Regulators - Linear
Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.75VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Package	-
Output TypeFixedNumber of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.75VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Series	-
Number of Regulators1Voltage - Input (Max)5.5 VVoltage - Output (Min/Fixed)2.75 VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Output Configuration	Positive
Voltage - Input (Max) Voltage - Output (Min/Fixed) 2.75V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 250mA Current - Quiescent (Iq) - Current - Supply (Max) PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Protection Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type Package / Case Supplier Device Package - Supplier Device Package	Output Type	Fixed
Voltage - Output (Min/Fixed)2.75 VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Number of Regulators	1
Voltage - Output (Max)-Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Voltage - Input (Max)	5.5V
Voltage Dropout (Max)-Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Voltage - Output (Min/Fixed)	2.75V
Current - Output250mACurrent - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Voltage - Output (Max)	-
Current - Quiescent (Iq)-Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Voltage Dropout (Max)	-
Current - Supply (Max)23μAPSRR91dB ~ 48dB (100Hz ~ 100kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Soft StartOperating Temperature-40°C ~ 125°C (TA)Mounting Type-Package / Case-Supplier Device Package-	Current - Output	250mA
PSRR 91dB ~ 48dB (100Hz ~ 100kHz) Control Features Enable Protection Features Over Current, Over Temperature, Soft Start Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package -	Current - Quiescent (Iq)	-
Control Features Protection Features Over Current, Over Temperature, Soft Start -40°C ~ 125°C (TA) Mounting Type - Package / Case Supplier Device Package - Enable Over Current, Over Temperature, Soft Start -40°C ~ 125°C (TA) - - - - - - - - - - - - -	Current - Supply (Max)	23μΑ
Protection Features Over Current, Over Temperature, Soft Start -40°C ~ 125°C (TA) Mounting Type - Package / Case Supplier Device Package - Over Current, Over Temperature, Soft Start -40°C ~ 125°C (TA)	PSRR	91dB ~ 48dB (100Hz ~ 100kHz)
Operating Temperature -40°C ~ 125°C (TA) Mounting Type - Package / Case - Supplier Device Package -	Control Features	Enable
Mounting Type - Package / Case - Supplier Device Package -	Protection Features	Over Current, Over Temperature, Soft Start
Package / Case - Supplier Device Package -	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

NCP160BMX275TBG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NCP160BMX275TBG Payment Methods



















NCP160BMX275TBG Shipping Methods













If you have any question about NCP160BMX275TBG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com