



ND03P00333K-- Information

Heisener.com

Part NumberND03P00333K--ManufacturerAVX CorporationCategorySensors, Transducers

Temperature Sensors - NTC Thermistors

Description NTC THERMISTOR 33K OHM 10% DISC

Package Disc, 3.5mm Dia x 3.0mm W

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ND03P00333K-- Specifications

Manufacturer Part Number ND03P00333K Manufacturer AVX Corporation Category Sensors, Transducers Package Disc, 3.5mm Dia x 3.0mm W Series ND03 Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	*	
Category Sensors, Transducers Temperature Sensors - NTC Thermistors Package Disc, 3.5mm Dia x 3.0mm W Series ND03 Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Manufacturer Part Number	ND03P00333K
Package Disc, 3.5mm Dia x 3.0mm W Series ND03 Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Manufacturer	AVX Corporation
Package Disc, 3.5mm Dia x 3.0mm W Series ND03 Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Category	Sensors, Transducers
Series ND03 Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C 33k Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Package	Disc, 3.5mm Dia x 3.0mm W
Resistance Tolerance ±10% B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Series	ND03
B Value Tolerance ±2% B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Resistance in Ohms @ 25°C	33k
B0/50 - B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Resistance Tolerance	±10%
B25/50 - B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B Value Tolerance	±2%
B25/75 - B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B0/50	-
B25/85 4220K B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B25/50	-
B25/100 - Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B25/75	-
Operating Temperature -55°C ~ 150°C Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B25/85	4220K
Power - Max 250mW Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	B25/100	-
Length - Lead Wire 1.38" (35.00mm) Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Operating Temperature	-55°C ~ 150°C
Mounting Type Through Hole Package / Case Disc, 3.5mm Dia x 3.0mm W	Power - Max	250mW
Package / Case Disc, 3.5mm Dia x 3.0mm W	Length - Lead Wire	1.38" (35.00mm)
	Mounting Type	Through Hole
Report errors?	Package / Case	Disc, 3.5mm Dia x 3.0mm W
		Report errors?

ND03P00333K-- Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ND03P00333K-- Payment Methods



















ND03P00333K-- Shipping Methods













If you have any question about ND03P00333K--, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com