

NF4EB-6V Information



For Reference Only

Part Number NF4EB-6V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE 4PDT 2A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NF4EB-6V Specifications

Manufacturer Part NumberNF4EB-6VManufacturerPanasonic Electric WorksCategoryRelaysBackage-SeriesNFRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesNFRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	NF4EB-6V
Package-SeriesNFRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series NF Relay Type General Purpose Coil Type Non Latching Coil Current 43.33mA Coil Voltage 6VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesNFRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current43.33mACoil Voltage6VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage220VAC, 220VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	NF
Coil Current 43.33mA Coil Voltage 6VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	43.33mA
Contact Rating (Current) Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	6VDC
Switching Voltage 220VAC, 220VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Mounting Type Through Hole Termination Style 4.8 VDC 1.5ms 1.	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style O.6 VDC 15ms 15ms 10ms PC Pin	Switching Voltage	220VAC, 220VDC - Max
Operate Time 15ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.8 VDC
Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

NF4EB-6V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NF4EB-6V Payment Methods





















NF4EB-6V Shipping Methods













If you have any question about NF4EB-6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com