

### NFS110-7605

#### NFS110-7605 Information

		NFS110-7605 Artesyn Embedded Technologies	
Catego		Power Supplies - External/Internal (Off-Board)	
Descr	ription	AC DC Converters AC/DC CONVERTER 5.1V 80W	
Pack	age	- For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### NFS110-7605 Specifications

Manufacturer Part NumberNFS 110-7605ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)Package-Package-SeriesNFS 110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4SMV (100 Forced Air)Voltage - Output 5SWV (100 Forced Air)Voltage - Output 6-Voltage - Output 7SMV (100 Forced Air)Voltage - Output 6SWV (100 Forced Air)Price inspace3kV (3000V)Efficiency0%Operating TemperatureMissible Output, DC Input Capable, Universal InputMounting TypeChasis MountSize / Dimension1,00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)				
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4Max)8APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency0%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting Type5.10° Lx 4.25° Wx 1.80° H (177.8mm x 108.0mm x 45.7mm)	Manufacturer Part Number	NFS110-7605		
AckageAC DC ConvertersPackage-SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)SW (110W Forced Air)Voltage - IsolationSW (110W Forced Air)Voltage - Isolation9W (110W Forced Air)Poter (Matts)9W (100W Forced Air)Poter (Watts)9W (100W Forced Air)Feficiency0% (2000V)Efficiency0% (300V)FeaturesAdjustable Output, DC Input Capable, Universal InputFeaturesAdjustable Output, DC Input Capable, Universal InputMounting Type7.0° L x 4.25" W x 1.80" H (177.8m x 108.0m x 45.7mm)	Manufacturer	Artesyn Embedded Technologies		
Package.SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 4.Voltage - Output 4.Voltage - Output 5.Voltage - Output 6.Voltage - Output 7.Voltage - Output 7.Voltage - Output 8.Voltage - Output 9.Voltage - Output 9.Voltage - Output 1.Voltage - Output 1.Voltage - Output 4.Voltage - Output 5.Voltage - Output 6.Voltage - Output 7.Voltage - Solation.Voltage - Isolation.Voltage - Isolation.Voltage - Solation.Voltage - Solatio	Category	Power Supplies - External/Internal (Off-Board)		
SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)80W (110W Forced Air)ApplicationsTE (Commercial)Voltage - Isolation3kV (3000V)Efficiency0%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustabe Output, DC Input Capable, Universal InputMounting Type7.00° L x 4.25° W x 1.80° H (177.8mm x 108.0mm x 45.7mm)		AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 484Power (Watts)80W (110W Forced Air)Applications1FE (Commercial)Voltage - Isolation3kV (3000V)Efficiency0%Operating TemperatureOic ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeCassi MountSize / Dinension7.0° L x 4.25° W x 1.80° H (177.8mm x 108.0mm x 45.7mm)	Package	-		
Number of Outputs         I           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5.1V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8A           Power (Watts)         80W (110W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chasis Mount           Size / Dimension         7.00° L x 4.25° W x 1.80° H (177.8mm x 108.0mm x 45.7mm)	Series	NFS110		
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5.1V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Voltage - Output 4         -           Current - Output (Max)         8A           Power (Watts)         80W (110W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         O'C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Туре	Open Frame		
Voltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating TemperatureO'C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting Type7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8A           Power (Watts)         80W (110W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 1	5.1V		
Voltage - Output 4-Current - Output (Max)8APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 2	-		
Current - Output (Max)8APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 3	-		
Power (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 4	-		
Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Current - Output (Max)	8A		
Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Power (Watts)	80W (110W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Efficiency	70%		
Mounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Operating Temperature	$0^{\circ}$ C ~ $70^{\circ}$ C (With Derating)		
Size / Dimension       7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Features	Adjustable Output, DC Input Capable, Universal Input		
	Mounting Type	Chassis Mount		
	Size / Dimension	7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)		
Report errors?		Report errors		

#### NFS110-7605 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# NFS110-7605 Payment Methods WIRE PayPal PayPal Power Power

If you have any question about NFS110-7605, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com