

# NFS110-7624J

### NFS110-7624J Information

Heisener.com	 NFS110-7624J Artesyn Embedded Technologies Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# NFS110-7624J Specifications

ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4-Voltage - Output 4-Voltage - Output 43.5APower (Wats)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (300V)Efficiency0°C ~ 70°C (With Derating)PeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChasis Mount				
CategoryPower Supplies - External/Internal (Off-Board) AC DC ConvertersPackage-SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 43.5APower (Watts)80W (110W Forced Air)ApplicationsTFE (Commercial)Voltage - Isolation3.5V (300V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChasis MountSize / Dimension7.00° L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Manufacturer Part Number	NFS110-7624J		
AC DC Converters   Package -   Series NFS110   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output 4 -   Voltage - Output 4 -   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (300V)   Efficiency 75%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chasis Mount   Size / Dimension 7.00° L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Manufacturer	Artesyn Embedded Technologies		
Package-SeriesNFS110TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4S.SAPower (Watts)80W (110W Forced Air)Voltage - Isolation3kV (3000V)Efficiency0°C ~ 70°C (With Derating)Operating TemperatureAdjustable Output, DC Input Capable, Universal InputSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series NFS110   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.5A   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 75%   Operating Temperature Adjustable Output, DC Input Capable, Universal Input   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)		AC DC Converters		
Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 5 -   Voltage - Output 6 -   Voltage - Output 7 -   Voltage - Solation 3.5A   Voltage - Isolation Six (3000V)   Efficiency 75%   Operating Temperature O'C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chasis Mount   Siz / Dimension 7.00° L x 4.25° W x 1.80° H (177.8mm x 108.0mm x 45.7mm)	Package	-		
Number of Outputs I   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.5A   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 75%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Series	NFS110		
Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.5A   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 75%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Туре	Open Frame		
Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.5A   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 75%   Operating Temperature O°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Number of Outputs	1		
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.5A   Power (Watts) 80W (110W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 75%   Operating Temperature 0°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.00° L x 4.25° W x 1.80° H (177.8mm x 108.0mm x 45.7mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)3.5APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 1	24V		
Voltage - Output 4-Current - Output (Max)3.5APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 2	-		
Current - Output (Max)3.5APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)PeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 3	-		
Power (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Current - Output (Max)	3.5A		
Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Power (Watts)	80W (110W Forced Air)		
Efficiency75%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Efficiency	75%		
Mounting Type Chassis Mount   Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Operating Temperature	$0^{\circ}C \sim 70^{\circ}C$ (With Derating)		
Size / Dimension 7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)	Features	Adjustable Output, DC Input Capable, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	7.00" L x 4.25" W x 1.80" H (177.8mm x 108.0mm x 45.7mm)		
			Report errors?	

#### NFS110-7624J Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# NFS110-7624J Payment Methods



# NFS110-7624J Shipping Methods



If you have any question about NFS110-7624J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com