



NH1M224 Information

Heisener.com

Part Number NH1M224
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQUARE 224A 500VAC/440VDC

Package Fuse Link

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NH1M224 Specifications

Manufacturer Part Number NH1M224 Manufacturer Littelfuse Inc. Category Circuit Protection Package Fuse Link Series - Fuse Type Square Current Rating 224A Voltage Rating - AC 500V Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Fuse Link Series - Fuse Type Square Current Rating 224A Voltage Rating - AC 500V Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Manufacturer Part Number	NH1M224
PackageElectrical, Specialty FusesPackageFuse LinkSeries-Fuse TypeSquareCurrent Rating224AVoltage Rating - AC500VVoltage Rating - DC440VResponse TimeFastApplicationsMotor ProtectionFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 25kA DCMounting TypeHolderPackage / CaseFuse LinkSize / Dimension5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Manufacturer	Littelfuse Inc.
Package Fuse Link Series - Fuse Type Square Current Rating 224A Voltage Rating - AC 500V Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Category	Circuit Protection
Series - Fuse Type Square Current Rating 224A Voltage Rating - AC 500V Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating224AVoltage Rating - AC500VVoltage Rating - DC440VResponse TimeFastApplicationsMotor ProtectionFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 25kA DCMounting TypeHolderPackage / CaseFuse LinkSize / Dimension5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Package	Fuse Link
Current Rating 224A Voltage Rating - AC 500V Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC 440V Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V 440V 500V 440V 440V 440V 440V 440V 440V Fast Fast Approvals NH Approvals VDE	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Fuse Link Size / Dimension Fast Motor Protection Motor Protection Motor Protection Lass NH VDE Liky VDE VDE - Holder Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Current Rating	224A
Response Time Fast Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Voltage Rating - AC	500V
Applications Motor Protection Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Voltage Rating - DC	440V
Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Response Time	Fast
Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Applications	Motor Protection
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Fuse Link Size / Dimension VDE - Link VDE - Link Size / Dimension VDE - Link VDE - Link Size / Dimension	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Class	NH
Breaking Capacity @ Rated Voltage 120kA AC, 25kA DC Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Approvals	VDE
Mounting Type Holder Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Operating Temperature	-
Package / Case Fuse Link Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Breaking Capacity @ Rated Voltage	120kA AC, 25kA DC
Size / Dimension 5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)	Mounting Type	Holder
	Package / Case	Fuse Link
Report errors?	Size / Dimension	5.315" L x 2.532" W x 1.575" H (135.00mm x 64.30mm x 40.00mm)
		Report errors?

NH1M224 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NH1M224 Payment Methods



















NH1M224 Shipping Methods













If you have any question about NH1M224, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com