



NITD20M32 Information

w.heisener.com

For Reference Only

Part Number NITD20M32

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 32A 550VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NITD20M32 Specifications

Manufacturer Part NumberNITD20M32ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Manufacturer Part Number	NITD20M32
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Category	Circuit Protection
SeriesNITDFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC S50V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension	Series	NITD
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 550V 550V 550V 560V 560V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class Cylindrical, Blade Terminal (Bolt) Class	Current Rating	32A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case - Cylindrical, Blade Terminal (Bolt) Size / Dimension - O.539" Dia x 1.362" L (13.70mm x 34.60mm)	Voltage Rating - AC	550V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Service Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.539" Dia x 1.362" L (13.70mm x 34.60mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.539" Dia x 1.362" L (13.70mm x 34.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.539" Dia x 1.362" L (13.70mm x 34.60mm)
		Report errors?

NITD20M32 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NITD20M32 Payment Methods



















NITD20M32 Shipping Methods













If you have any question about NITD20M32, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com