



NITD32M50 Information

w helsener.com

For Reference Only

Part Number NITD32M50

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 50A 415VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NITD32M50 Specifications

Manufacturer Part NumberNITD32M50ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Manufacturer Part Number	NITD32M50
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesNITDFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Category	Circuit Protection
SeriesNITDFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 415V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 50A 415V 4	Series	NITD
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 415V 415V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class -	Current Rating	50A
Response Time - Applications Electrical, Industrial Features - Class	Voltage Rating - AC	415V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.689" Dia x 1.398" L (17.50mm x 35.50mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.689" Dia x 1.398" L (17.50mm x 35.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.689" Dia x 1.398" L (17.50mm x 35.50mm)
		Report errors?

NITD32M50 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NITD32M50 Payment Methods



















NITD32M50 Shipping Methods













If you have any question about NITD32M50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com