



NJM2060M Information



For Reference Only

Part Number NJM2060M

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 10MHZ 14DMP **Package** 14-SOIC (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM2060M Specifications

Manufacturer Part Number NJM2060M Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 4 V/µs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 40nA Voltage - Input Offset 500µV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.209", 5.30mm Width) Series -	Manufacturer Part Number	NJM2060M
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 4 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 40nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Manufacturer	NJR Corporation/NJRC
Package 14-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 4 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 40nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 4 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 40nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeGeneral PurposeNumber of Circuits4Output Type-Slew Rate4 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias40nAVoltage - Input Offset500μVCurrent - Supply9mACurrent - Output / Channel-Voltage - Supply, Single/Dual (±)±4 V ~ 18 VOperating Temperature-20°C ~ 75°CMounting TypeSurface MountPackage / Case14-SOIC (0.209", 5.30mm Width)Supplier Device Package14-DMP	Package	14-SOIC (0.209", 5.30mm Width)
Number of Circuits 4 Output Type - Slew Rate 4 $V/\mu s$ Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 40nA Voltage - Input Offset 500 μV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) \pm 4 $V \sim 18 V$ Operating Temperature $-20^{\circ}C \sim 75^{\circ}C$ Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Series	-
Output Type - Slew Rate $4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 10MHz - 3db Bandwidth Product 4DnHz - 4Current - Input Bias 4OnA Voltage - Input Offset 4DnHz - 4Current - Supply 4DnHz - 4Current - $4 Curre$	Amplifier Type	General Purpose
Slew Rate $4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 10MHz -3db Bandwidth $-$ Current - Input Bias 40nA Voltage - Input Offset $500 \mu\text{V}$ Current - Supply 9mA Current - Output / Channel $-$ Voltage - Supply, Single/Dual (\pm) $\pm 4 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Number of Circuits	4
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 44 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package	Output Type	-
$-3 db \ Bandwidth \\ -Current - Input \ Bias \\ Voltage - Input \ Offset \\ 500 \mu V \\ Current - Supply \\ 9mA \\ Current - Output / Channel \\ -Voltage - Supply, Single/Dual (\pm) \pm 4 \ V \sim 18 \ V Operating Temperature -20^{\circ}\text{C} \sim 75^{\circ}\text{C} Mounting Type Surface Mount Package / Case 14\text{-SOIC }(0.209^{\circ}, 5.30 \text{mm Width}) Supplier Device Package 14\text{-DMP}$	Slew Rate	4 V/μs
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Gain Bandwidth Product	10MHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply 9mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Current - Input Bias	40nA
Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±4 V ~ 18 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Voltage - Input Offset	$500\mu V$
Voltage - Supply, Single/Dual (\pm) ± 4 V ~ 18 V Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Current - Supply	9mA
Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Current - Output / Channel	-
Mounting Type Surface Mount Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Voltage - Supply, Single/Dual (±)	±4 V ~ 18 V
Package / Case 14-SOIC (0.209", 5.30mm Width) Supplier Device Package 14-DMP	Operating Temperature	-20°C ~ 75°C
Supplier Device Package 14-DMP	Mounting Type	Surface Mount
	Package / Case	14-SOIC (0.209", 5.30mm Width)
Domont among	Supplier Device Package	14-DMP
Report errors		Report errors?

NJM2060M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM2060M Payment Methods





















NJM2060M Shipping Methods













If you have any question about NJM2060M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com