

NJM2122D# Information

ne ener.com

For Reference Only

Part Number NJM2122D#

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 12MHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM2122D# Specifications

Manufacturer Part Number NJM2122D# Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 2.4 V/μs Gain Bandwidth Product 12MHz -3db Bandwidth - Current - Input Bias 3.6μA Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP		
Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps	Manufacturer Part Number	NJM2122D#
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 2.4 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 3.6µA Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Manufacturer	NJR Corporation/NJRC
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 2.4 V/μs Gain Bandwidth Product 12MHz -3db Bandwidth - Current - Input Bias 3.6μA Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 2.4 V/μs Gain Bandwidth Product 12MHz -3db Bandwidth - Current - Input Bias 3.6μA Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 2 Output Type - Slew Rate 2.4 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Voperating Temperature -20°C ~ 75°C Mounting Type Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 2.4 V/μs Gain Bandwidth Product 12MHz -3db Bandwidth - Current - Input Bias 3.6μA Voltage - Input Offset 1mV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Series	-
Output Type - Slew Rate - 2.4 V/ μ s Gain Bandwidth Product - 12MHz -3db Bandwidth Current - Input Bias - 3.6 μ A Voltage - Input Offset - 1mV Current - Supply - 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) - 2 V ~ 10 V Operating Temperature - 20°C ~ 75°C Mounting Type - Through Hole Package / Case - 8-DIP (0.300", 7.62mm) Supplier Device Package - 8-DIP	Amplifier Type	General Purpose
Slew Rate 2.4 V/µs Gain Bandwidth Product 12MHz -3db Bandwidth - Current - Input Bias 3.6µA Voltage - Input Offset 1mV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) \pm 2 V ~ 10 V Operating Temperature \pm 20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 3.6μA Voltage - Input Offset ImV Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) Operating Temperature -20°C ~ 75°C Mounting Type Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Output Type	-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Slew Rate	$2.4 \text{ V/}\mu\text{s}$
Current - Input Bias $3.6\mu A$ Voltage - Input Offset $1mV$ Current - Supply $7mA$ Current - Output / Channel - Voltage - Supply, Single/Dual (±) $\pm 2 \ V \sim 10 \ V$ Operating Temperature $-20^{\circ}C \sim 75^{\circ}C$ Mounting Type $Through\ Hole$ Package / Case 8 -DIP $(0.300'', 7.62mm)$ Supplier Device Package 8 -DIP	Gain Bandwidth Product	12MHz
Voltage - Input Offset Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	-3db Bandwidth	-
Current - Supply 7mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Input Bias	3.6μΑ
Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) \pm 2 V ~ 10 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Voltage - Input Offset	1mV
Voltage - Supply, Single/Dual (\pm) ± 2 V ~ 10 V Operating Temperature -20° C ~ 75° C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Supply	7mA
Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Output / Channel	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Voltage - Supply, Single/Dual (±)	±2 V ~ 10 V
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 75°C
Supplier Device Package 8-DIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Panort arrors	Supplier Device Package	8-DIP
Report errors		Report errors?

NJM2122D# Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM2122D# Payment Methods



















NJM2122D# Shipping Methods













If you have any question about NJM2122D#, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com