

NJM2732M Information



For Reference Only

Part Number NJM2732M

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 1MHZ RRO 8DMP **Package** 8-SOIC (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM2732M Specifications

Manufacturer Part Number NJM2732M Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product IMHz -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset ImV Current - Supply 580μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP		
Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps	Manufacturer Part Number	NJM2732M
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product IMHz -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset ImV Current - Supply 580μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Manufacturer	NJR Corporation/NJRC
Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 1MHz -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset 1mV Current - Supply 580μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 1MHz -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset 1mV Current - Supply 580μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset ImV Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -40°C ~ 85°C Mounting Type Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package	Package	8-SOIC (0.209", 5.30mm Width)
Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/ μ s Gain Bandwidth Product 1MHz -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset 1mV Current - Supply 580 μ A Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Series	-
Output Type Rail-to-Rail Slew Rate 0.4 V/ μ s Gain Bandwidth Product 1MHz -3db Bandwidth Current - Input Bias 50nA Voltage - Input Offset 1mV Current - Supply 580 μ A Current - Output / Channel Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 1mV Current - Supply 580µA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature 40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset ImV Current - Supply 580µA Current - Output / Channel Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package	Output Type	Rail-to-Rail
-3db Bandwidth - Current - Input Bias 50nA Voltage - Input Offset 1mV Current - Supply 580μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Slew Rate	0.4 V/μs
Current - Input Bias $50nA$ Voltage - Input Offset $1mV$ Current - Supply $580\mu A$ Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) $1.8 \ V \sim 6 \ V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount Package / Case 8 -SOIC (0.209° , $5.30mm$ Width) Supplier Device Package 8 -DMP	Gain Bandwidth Product	1MHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply 580µA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Current - Input Bias	50nA
Current - Output / Channel - Voltage - Supply, Single/Dual (±) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Voltage - Input Offset	1mV
Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Current - Supply	580μΑ
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Current - Output / Channel	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Voltage - Supply, Single/Dual (±)	1.8 V ~ 6 V
Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 8-DMP	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.209", 5.30mm Width)
	Supplier Device Package	8-DMP
Report errors		Report errors?

NJM2732M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM2732M Payment Methods



















NJM2732M Shipping Methods













If you have any question about NJM2732M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com