



NJM2904D Information



For Reference Only

Part Number NJM2904D

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 600KHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM2904D Specifications

Manufacturer Part Number NJM2904D Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.5 V/µs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700µA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.5 V/μs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Manufacturer Part Number	NJM2904D
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.5 V/μs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Manufacturer	NJR Corporation/NJRC
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.5 V/μs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Category	Integrated Circuits (ICs)
Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate0.5 V/μsGain Bandwidth Product600kHz-3db Bandwidth-Current - Input Bias25nAVoltage - Input Offset2mVCurrent - Supply700μACurrent - Output / Channel30mAVoltage - Supply, Single/Dual (±)3 V ~ 32 V, ±1.5 V ~ 16 VOperating Temperature-40°C ~ 85°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate0.5 V/μsGain Bandwidth Product600kHz-3db Bandwidth-Current - Input Bias25nAVoltage - Input Offset2mVCurrent - Supply700μACurrent - Output / Channel30mAVoltage - Supply, Single/Dual (±)3 V ~ 32 V, ±1.5 V ~ 16 VOperating Temperature-40°C ~ 85°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIP	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 0.5 V/μs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Series	-
Output Type Slew Rate 0.5 V/µs Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700µA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Amplifier Type	General Purpose
Slew Rate 0.5 V/ μ s Gain Bandwidth Product 600kHz -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700 μ A Current - Output / Channel 30mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 32 V, \pm 1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 25nA Voltage - Input Offset 2mV Current - Supply 700µA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Output Type	-
$-3 db \ Bandwidth \\ Current - Input \ Bias \\ 25 nA \\ Voltage - Input \ Offset \\ 2 mV \\ Current - Supply \\ 700 \mu A \\ Current - Output / Channel \\ 30 mA \\ Voltage - Supply, Single/Dual (\pm) 3 \ V \sim 32 \ V, \pm 1.5 \ V \sim 16 \ V \\ Operating \ Temperature \\ -40^{\circ}C \sim 85^{\circ}C \\ Mounting \ Type \\ Package / Case \\ 8-DIP (0.300'', 7.62 mm) \\ Supplier \ Device \ Package \\ 8-DIP$	Slew Rate	0.5 V/μs
Current - Input Bias $25nA$ Voltage - Input Offset $2mV$ Current - Supply $700\mu A$ Current - Output / Channel $30mA$ Voltage - Supply, Single/Dual (\pm) $3V \sim 32V, \pm 1.5V \sim 16V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Through Hole Package / Case 8 -DIP $(0.300^{\circ}, 7.62mm)$ Supplier Device Package 8 -DIP	Gain Bandwidth Product	600kHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply 700 μ A Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 32 V, ±1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Input Bias	25nA
Current - Output / Channel $30mA$ Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 32 \text{ V}, \pm 1.5 \text{ V} \sim 16 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeThrough HolePackage / Case 8-DIP (0.300° , $7.62mm$)Supplier Device Package 8-DIP	Voltage - Input Offset	2mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 32 V, \pm 1.5 V ~ 16 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Supply	700μΑ
Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Output / Channel	30mA
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Voltage - Supply, Single/Dual (±)	3 V ~ 32 V, ±1.5 V ~ 16 V
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 8-DIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-DIP
report offors.		Report errors?

NJM2904D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM2904D Payment Methods





















NJM2904D Shipping Methods













If you have any question about NJM2904D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com