



NJM5534D Information



For Reference Only

Part Number NJM5534D

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 10MHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM5534D Specifications

Manufacturer Part Number NJM5534D Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 13 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500μV Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 13 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500µV Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Manufacturer Part Number	NJM5534D
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits1Output Type-Slew Rate13 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias500nAVoltage - Input Offset500μVCurrent - Supply4mACurrent - Output / Channel-Voltage - Supply, Single/Dual (±)±3 V ~ 22 VOperating Temperature-20°C ~ 75°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIP	Manufacturer	NJR Corporation/NJRC
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 13 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500μV Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Category	Integrated Circuits (ICs)
Series - General Purpose Number of Circuits 1 Output Type - Slew Rate 13 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500μV Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeGeneral PurposeNumber of Circuits1Output Type-Slew Rate13 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias500nAVoltage - Input Offset500μVCurrent - Supply4mACurrent - Output / Channel-Voltage - Supply, Single/Dual (±)±3 V ~ 22 VOperating Temperature-20°C ~ 75°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIP	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 1 Output Type - Slew Rate 13 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500μV Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Series	-
Output Type Slew Rate 13 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500µV Current - Supply 4mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 43 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Amplifier Type	General Purpose
Slew Rate 13 V/ μ s Gain Bandwidth Product 10MHz -3db Bandwidth	Number of Circuits	1
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 500nA Voltage - Input Offset 500μV Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 4πA Current - Output / Channel - Current - Output / C	Output Type	-
$-3 db \ Bandwidth \\ -Current - Input \ Bias \\ 500 nA \\ Voltage - Input \ Offset \\ 500 \mu V \\ Current - Supply \\ 4mA \\ Current - Output / Channel \\ -Voltage - Supply, Single/Dual (\pm) \pm 3 \ V \sim 22 \ V \\ Operating \ Temperature \\ -20^{\circ}C \sim 75^{\circ}C \\ Mounting \ Type \\ Through \ Hole \\ Package / Case \\ 8-DIP (0.300'', 7.62mm) \\ Supplier \ Device \ Package \\ 8-DIP$	Slew Rate	13 V/μs
Current - Input Bias $500nA$ Voltage - Input Offset $500\mu V$ Current - Supply $4mA$ Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) $\pm 3 \ V \sim 22 \ V$ Operating Temperature $-20^{\circ}C \sim 75^{\circ}C$ Mounting Type Through Hole Package / Case 8 -DIP $(0.300^{\circ}, 7.62mm)$ Supplier Device Package 8 -DIP	Gain Bandwidth Product	10MHz
Voltage - Input Offset	-3db Bandwidth	-
Current - Supply 4mA Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Input Bias	500nA
Current - Output / Channel - Voltage - Supply, Single/Dual (±) ±3 V ~ 22 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Voltage - Input Offset	500μV
Voltage - Supply, Single/Dual (\pm) ± 3 V ~ 22 V Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Supply	4mA
Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Current - Output / Channel	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Voltage - Supply, Single/Dual (±)	$\pm 3 \text{ V} \sim 22 \text{ V}$
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 75°C
Supplier Device Package 8-DIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-DIP
		Report errors?

NJM5534D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM5534D Payment Methods





















NJM5534D Shipping Methods













If you have any question about NJM5534D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com