



NJU7062M Information



For Reference Only

Part Number NJU7062M

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 400KHZ RRO 8DMP **Package** 8-SOIC (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJU7062M Specifications

Manufacturer Part Number NJU7062M Manufacturer NJR Corporation/NJRC Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 400kHz -3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP		
Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps	Manufacturer Part Number	NJU7062M
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 400kHz -3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Manufacturer	NJR Corporation/NJRC
Package 8-SOIC (0.209", 5.30mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 400kHz -3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/μs Gain Bandwidth Product 400kHz -3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 2mV Current - Supply 150µA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package	Package	8-SOIC (0.209", 5.30mm Width)
Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.4 V/ μ s Gain Bandwidth Product 400kHz -3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150 μ A Current - Output / Channel Voltage - Supply, Single/Dual (\pm) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Series	-
Output Type Rail-to-Rail Slew Rate 0.4 V/ μ s Gain Bandwidth Product 400kHz -3db Bandwidth Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150 μ A Current - Output / Channel Voltage - Supply, Single/Dual (\pm) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset Current - Supply Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 0.4 V/µs 400kHz - 100kHz - 2mV 2mV 2mV 2mV 2mV 2mV 2mV	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 2mV Current - Supply 150µA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package	Output Type	Rail-to-Rail
-3db Bandwidth - Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Slew Rate	0.4 V/μs
Current - Input Bias 1pA Voltage - Input Offset 2mV Current - Supply 150 μ A Current - Output / Channel - Voltage - Supply, Single/Dual (\pm) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Gain Bandwidth Product	400kHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply $150\mu A$ Current - Output / Channel - Voltage - Supply, Single/Dual (±) $3 \text{ V} \sim 16 \text{ V}$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case $8\text{-SOIC }(0.209^{\circ}, 5.30\text{mm Width})$ Supplier Device Package 8-DMP	Current - Input Bias	1pA
$\begin{tabular}{lll} Current - Output / Channel & - & & & & & & & & & & & & & & & & & $	Voltage - Input Offset	2mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 16 V Operating Temperature -20°C ~ 75°C Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Current - Supply	150μΑ
Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Current - Output / Channel	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Voltage - Supply, Single/Dual (±)	3 V ~ 16 V
Package / Case 8-SOIC (0.209", 5.30mm Width) Supplier Device Package 8-DMP	Operating Temperature	-20°C ~ 75°C
Supplier Device Package 8-DMP	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.209", 5.30mm Width)
	Supplier Device Package	8-DMP
Report errors		Report errors?

NJU7062M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJU7062M Payment Methods





















NJU7062M Shipping Methods













If you have any question about NJU7062M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com