

NL6EBX-L2-DC48V-1

NL6EBX-L2-DC48V-1 Information

Heisener.com	 NL6EBX-L2-DC48V-1 Panasonic Electric Works Relays Signal Relays, Up to 2 Amps RELAY GEN PURPOSE 6PDT 2A 48V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



NL6EBX-L2-DC48V-1 Specifications

Manufacturer Part Number NL6EBX-L2-DC48V-1 Manufacturer Panasonic Electric Works Category Relays Category Signal Relays, Up to 2 Amps Package - Series NL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 33.mA Coil Voltage 48VDC Contact Form GPDT (6 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 30VDC - Max Turn On Voltage (Max) 38.4 VDC Querter Time Ioms Release Time Ioms Features - Mounting Type PC Pin		
CategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesNLRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current33.3mACoil Voltage48VDCContact FormOPDT (6 Form C)Contact Rating (Current)2ASwitching Voltage (Max)38.4 VDCTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease TimeIomsFeatures-Mounting TypeFinoigh HoleTermination StyleCP In	Manufacturer Part Number	NL6EBX-L2-DC48V-1
Signal Relays, Up to 2 AmpsPackage-SeriesNLRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current33.3mACoil Voltage48VDCContact FormOPDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesNLRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Type33.3mACoil Ourent33.3mACoil Voltage6PDT (6 Form C)Contact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeChong HoleTermination StylePC Pin	Category	Relays
SeriesNLRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Type33.3mACoil Current33.3mACoil Voltage48VDCContact FormOPDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination Style9C Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Type33.3mACoil Outage48VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current33.3mACoil Voltage48VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)88.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	NL
Coil Current33.3mACoil Voltage48VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage48VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Type	Latching, Dual Coil
Contact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Current	33.3mA
Contact Rating (Current)2ASwitching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	48VDC
Switching Voltage125VAC, 30VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Form	6PDT (6 Form C)
Turn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	125VAC, 30VDC - Max
Operate Time15msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	38.4 VDC
Release Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	-
Features-Mounting TypeThrough HoleTermination StylePC Pin	Operate Time	15ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	10ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors	Termination Style	PC Pin
		Report errors?

NL6EBX-L2-DC48V-1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

NL6EBX-L2-DC48V-1 Payment Methods



NL6EBX-L2-DC48V-1 Shipping Methods



If you have any question about NL6EBX-L2-DC48V-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com