



#### **NLAS4684MR2 Information**



For Reference Only

Part Number NLAS4684MR2

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)

Interface - Analog Switches, Multiplexers,

**Demultiplexers** 

**Description** IC SWITCH DUAL SPDT MICRO10

**Package** 10-TFSOP, 10-MSOP (0.118", 3.00mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **NLAS4684MR2 Specifications**

Manufacturer Part NumberNLAS4684MR2ManufacturerON SemiconductorCategoryIntegrated Circuits (ICs)Interface - Analog Switches, Multiplexers, DemultiplexersPackage10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Series-Switch CircuitSPDTMultiplexer/Demultiplexer Circuit2:1Number of Circuits2On-State Resistance (Max)800 mOhmChannel-to-Channel Matching (Ron)60 mOhmVoltage - Supply, Single (V+)1.8 V ~ 5.5 VVoltage - Supply, Dual (V±)-Switch Time (Ton, Toff) (Max)30ns, 30ns-3db Bandwidth9.5MHzChannel Capacitance (CS(off), CD(off))102pF, 104pF
Category  Integrated Circuits (ICs) Interface - Analog Switches, Multiplexers, Demultiplexers  Package  10-TFSOP, 10-MSOP (0.118", 3.00mm Width)  Series  - Switch Circuit  SPDT  Multiplexer/Demultiplexer Circuit  2:1  Number of Circuits  2  On-State Resistance (Max)  Channel-to-Channel Matching (Ron)  Voltage - Supply, Single (V+)  Voltage - Supply, Dual (V±)  Switch Time (Ton, Toff) (Max)  -3db Bandwidth  Charge Injection  Integrated Circuits (ICs)  Interface - Analog Switches, Multiplexers, Demultiplexers  - SPDT  SPDT  2:1  Number of Circuits  2  On-State Resistance (Max)  800 mOhm  Subjection  1.8 V ~ 5.5 V  Switch Time (Ton, Toff) (Max)  30ns, 30ns  Subjection  15pC
Interface - Analog Switches, Multiplexers, Demultiplexers  Package 10-TFSOP, 10-MSOP (0.118", 3.00mm Width)  Series - Switch Circuit SPDT  Multiplexer/Demultiplexer Circuit 2:1  Number of Circuits 2 On-State Resistance (Max) 800 mOhm  Channel-to-Channel Matching (Ron) 60 mOhm  Voltage - Supply, Single (V+) 1.8 V ~ 5.5 V  Voltage - Supply, Dual (V±) - Switch Time (Ton, Toff) (Max) 30ns, 30ns  -3db Bandwidth 9.5MHz  Charge Injection 15pC
Package 10-TFSOP, 10-MSOP (0.118", 3.00mm Width)  Series -  Switch Circuit SPDT  Multiplexer/Demultiplexer Circuit 2:1  Number of Circuits 2  On-State Resistance (Max) 800 mOhm  Channel-to-Channel Matching (Ron) 60 mOhm  Voltage - Supply, Single (V+) 1.8 V ~ 5.5 V  Voltage - Supply, Dual (V±) -  Switch Time (Ton, Toff) (Max) 30ns, 30ns  -3db Bandwidth 9.5MHz  Charge Injection 15pC
Series - Switch Circuit SPDT  Multiplexer/Demultiplexer Circuit 2:1  Number of Circuits 2  On-State Resistance (Max) 800 mOhm  Channel-to-Channel Matching (Ron) 60 mOhm  Voltage - Supply, Single (V+) 1.8 V ~ 5.5 V  Voltage - Supply, Dual (V±) -  Switch Time (Ton, Toff) (Max) 30ns, 30ns  -3db Bandwidth 9.5MHz  Charge Injection 15pC
Switch Circuit  Multiplexer/Demultiplexer Circuit  2:1  Number of Circuits  2  On-State Resistance (Max)  800 mOhm  Channel-to-Channel Matching (Ron)  Voltage - Supply, Single (V+)  Voltage - Supply, Dual (V±)  Switch Time (Ton, Toff) (Max)  -3db Bandwidth  Charge Injection  SPDT  2:1  2:1  800 mOhm  60 mOhm  1.8 V ~ 5.5 V  -  Switch Time (Ton, Toff) (Max)  30ns, 30ns  -3db Bandwidth  9.5MHz  Charge Injection
Multiplexer/Demultiplexer Circuit2:1Number of Circuits2On-State Resistance (Max)800 mOhmChannel-to-Channel Matching (Ron)60 mOhmVoltage - Supply, Single (V+)1.8 V ~ 5.5 VVoltage - Supply, Dual (V±)-Switch Time (Ton, Toff) (Max)30ns, 30ns-3db Bandwidth9.5MHzCharge Injection15pC
Number of Circuits2On-State Resistance (Max)800 mOhmChannel-to-Channel Matching (Ron)60 mOhmVoltage - Supply, Single (V+)1.8 V ~ 5.5 VVoltage - Supply, Dual (V±)-Switch Time (Ton, Toff) (Max)30ns, 30ns-3db Bandwidth9.5MHzCharge Injection15pC
On-State Resistance (Max)  Channel-to-Channel Matching (Ron)  Voltage - Supply, Single (V+)  Voltage - Supply, Dual (V±)  Switch Time (Ton, Toff) (Max)  -3db Bandwidth  9.5MHz  Charge Injection  800 mOhm  1.8 V ~ 5.5 V
Channel-to-Channel Matching (Ron)  Voltage - Supply, Single (V+)  Voltage - Supply, Dual (V±)  Switch Time (Ton, Toff) (Max)  -3db Bandwidth  9.5MHz  Charge Injection  60 mOhm  1.8 V ~ 5.5 V  -  Swhytch Time (Ton, Toff) (Max)  1.8 V ~ 5.5 V  -  1.8 V ~ 5.5 V
Voltage - Supply, Single (V+) $ 1.8 \text{ V} \sim 5.5 \text{ V} $ Voltage - Supply, Dual (V $\pm$ ) $ - $ Switch Time (Ton, Toff) (Max) $ 30ns, 30ns $ -3db Bandwidth $ 9.5MHz $ Charge Injection $ 15pC $
Voltage - Supply, Dual (V±)  Switch Time (Ton, Toff) (Max)  -3db Bandwidth  9.5MHz  Charge Injection  15pC
Switch Time (Ton, Toff) (Max)  -3db Bandwidth  9.5MHz  Charge Injection  15pC
-3db Bandwidth 9.5MHz Charge Injection 15pC
Charge Injection 15pC
Channel Capacitance (CS(off), CD(off)) 102pF, 104pF
Current - Leakage (IS(off)) (Max) 1µA
Crosstalk -83dB @ 100kHz
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$
Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width)
Supplier Device Package 10-Micro
Report errors?

#### **NLAS4684MR2 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **NLAS4684MR2 Payment Methods**



















## **NLAS4684MR2 Shipping Methods**













If you have any question about NLAS4684MR2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com