

Heisener.com

NLDFT-1-BK-L-C120-M40B

NLDFT-1-BK-L-C120-M40B Information

Part Number NLDFT-1-BK-L-C120-M40B

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN LINE DRAIN CRIMP 1POS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLDFT-1-BK-L-C120-M40B Specifications

Manufacturer Part NumberNLDFT-1-BK-L-C120-M40BManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660AReport errors?		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer Part Number	NLDFT-1-BK-L-C120-M40B
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector Type Line Drain, Female Sockets Number of Positions 1 Shell Size - Insert - Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating Line Drain, Female Sockets 1 Line Drain, Female Sockets 1 Line Drain, Female Sockets 1 Locking Pin Line Drain, Female Sockets Locking Pin Line Drain Line Drain Line Drain Line Drain Line Drain Line Drain Line Drain Line Drain Line Drain Line Drain Line Line Drain Line	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Connector Type	Line Drain, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Orientation	Keyed
Contact Finish Silver Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Contact Finish	Silver
Current Rating 660A	Features	Locking Pin
	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

NLDFT-1-BK-L-C120-M40B Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLDFT-1-BK-L-C120-M40B Payment Methods



















NLDFT-1-BK-L-C120-M40B Shipping Methods













If you have any question about NLDFT-1-BK-L-C120-M40B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com