

Heisener.com

# NLDFT-1-BN-L-C107-M40B

### NLDFT-1-BN-L-C107-M40B Information

Part Number NLDFT-1-BN-L-C107-M40B

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN LINE DRAIN CRIMP 1POS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# NLDFT-1-BN-L-C107-M40B Specifications

Manufacturer Part Number       NLDFT-1-BN-L-C107-M40B         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Powerlock         Connector Type       Line Drain, Female Sockets         Number of Positions       1         Shell Size - Insert       -         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       Keyed         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Thermoplastic         Contact Finish       Silver         Features       Locking Pin         Voltage - Rated       1000VAC, 1500VDC         Current Rating       660A		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer Part Number	NLDFT-1-BN-L-C107-M40B
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector Type Line Drain, Female Sockets  Number of Positions 1 Shell Size - Insert - Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin  Voltage - Rated 1000VAC, 1500VDC Current Rating  Line Drain, Female Sockets  1 Line Drain, Female Sockets  1 Line Drain, Female Sockets  1 Locking Pin Line Drain, Female Sockets  Locking Pin Line Drain Line Drain  Line Drain Line Drain Line Drain  Line Drain Line Drain Line Drain Line Drain Line Drain Line Line Drain Line Drain Line Line Line Line Line Line Line Li	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Connector Type	Line Drain, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic  Contact Finish Silver Features Locking Pin  Voltage - Rated 1000VAC, 1500VDC  Current Rating	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Size, MIL	-
Fastening Type  Orientation  Keyed  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Thermoplastic  Contact Finish  Silver  Features  Locking Pin  Voltage - Rated  1000VAC, 1500VDC  Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Orientation	Keyed
Contact Finish Silver Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Locking Pin  Voltage - Rated 1000VAC, 1500VDC  Current Rating 660A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Contact Finish	Silver
Current Rating 660A	Features	Locking Pin
	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

#### NLDFT-1-BN-L-C107-M40B Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### NLDFT-1-BN-L-C107-M40B Payment Methods





















## NLDFT-1-BN-L-C107-M40B Shipping Methods













If you have any question about NLDFT-1-BN-L-C107-M40B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com