

Heisener.com

## NLDFT-2-BK-L-C240-M40A

### NLDFT-2-BK-L-C240-M40A Information

Part Number NLDFT-2-BK-L-C240-M40A

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN LINE DRAIN CRIMP 1POS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# NLDFT-2-BK-L-C240-M40A Specifications

Manufacturer Part Number       NLDFT-2-BK-L-C240-M40A         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Powerlock         Connector Type       Line Drain, Female Sockets         Number of Positions       1         Shell Size - Insert       -         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       Keyed         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Thermoplastic         Contact Finish       Silver         Features       Locking Pin         Voltage - Rated       1000VAC, 1500VDC         Current Rating       660A		
Category Circular Connectors Circular Connectors  Package - Series Powerlock Connector Type Line Drain, Female Sockets  Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated Current Rating  Cinnectors, Interconnects Circular Connectors  - Connectors - Connectors - Connectors - Connectors - Connectors - Connectors - Circular Connectors - Circular Connectors - Connectors - Connectors - Connectors - Connectors - Circular Connectors - Connectors - Connectors - Connectors - Circular Connec	Manufacturer Part Number	NLDFT-2-BK-L-C240-M40A
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector Type Line Drain, Female Sockets  Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic  Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating	Connector Type	Line Drain, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin  Voltage - Rated 1000VAC, 1500VDC Current Rating	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Orientation	Keyed
Contact Finish Silver Locking Pin Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Locking Pin  Voltage - Rated 1000VAC, 1500VDC  Current Rating 660A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Contact Finish	Silver
Current Rating 660A	Features	Locking Pin
	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

#### NLDFT-2-BK-L-C240-M40A Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### NLDFT-2-BK-L-C240-M40A Payment Methods



















## NLDFT-2-BK-L-C240-M40A Shipping Methods













If you have any question about NLDFT-2-BK-L-C240-M40A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com