

Heisener.com

# NLDFT-N-BK-L-C120-M40S

### NLDFT-N-BK-L-C120-M40S Information

Part Number NLDFT-N-BK-L-C120-M40S

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN LINE DRAIN CRIMP 1POS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## NLDFT-N-BK-L-C120-M40S Specifications

Manufacturer Part NumberNLDFT-N-BK-L-C120-M40SManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDCCurrent Rating660A		
Category Connectors, Interconnects Circular Connectors  Package - Series Powerlock Connector Type Line Drain, Female Sockets Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated  Connectors, Interconnects Cineuctors  Founctors Interconnects Cineuctors  - Connectors Interconnectors  - Connectors  - Connectors Interconnectors  - Connectors  - Connectors Interconnectors  - Connectors  - Connector	Manufacturer Part Number	NLDFT-N-BK-L-C120-M40S
Circular Connectors  Package - Series Powerlock Connector Type Line Drain, Female Sockets Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated  Circular Connectors  Powerlock Line Drain, Female Sockets  1  Reyel Line Drain, Female Sockets  1  Line Drain, Female Sockets  Silver  Locking Pin  Locking Pin  Line Drain, Female Sockets  Locking Pin	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Drain, Female SocketsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDC	Category	Connectors, Interconnects
Series Powerlock Connector Type Line Drain, Female Sockets Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC		Circular Connectors
Connector Type Line Drain, Female Sockets  Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Silver Features Voltage - Rated  Line Drain, Female Sockets  1  Line Drain, Female Sockets  -  Locking Pin Line Drain, Female Sockets  -  Locking Pin Lockock  Locking Pin Lockock	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDC	Series	Powerlock
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  Keyed  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Thermoplastic  Contact Finish  Silver  Features  Locking Pin  Voltage - Rated	Connector Type	Line Drain, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDC	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  Keyed  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Thermoplastic  Contact Finish  Silver  Features  Locking Pin  Voltage - Rated  1000VAC, 1500VDC	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeaturesLocking PinVoltage - Rated1000VAC, 1500VDC	Orientation	Keyed
Contact Finish Silver Features Locking Pin Voltage - Rated 1000VAC, 1500VDC	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Locking Pin Voltage - Rated 1000VAC, 1500VDC	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC	Contact Finish	Silver
	Features	Locking Pin
Current Rating 660A	Voltage - Rated	1000VAC, 1500VDC
	Current Rating	660A
Report errors?		Report errors?

### NLDFT-N-BK-L-C120-M40S Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## NLDFT-N-BK-L-C120-M40S Payment Methods


































If you have any question about NLDFT-N-BK-L-C120-M40S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com