



## NLP110-9908 Information

Heisener.com

Part Number NLP110-9908

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 12V 5V -12V 80W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP110	9000	Specifi	antions
NLPIII	リーソソいる	Speciii	cauons

Manufacturer Part Number         NLP110-9908           Manufacturer         Artesyn Embedded Technologies           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         NLP110           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)				
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         NLP110           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         - 12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP110-9908		
Package         -           Series         NLP110           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies		
Package         -           Series         NLP110           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series         NLP110           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)		AC DC Converters		
Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Package	-		
Number of Outputs       3         Voltage - Input       90 ~ 264 VAC         Voltage - Output 1       12V         Voltage - Output 2       5V         Voltage - Output 3       -12V         Voltage - Output 4       -         Current - Output (Max)       6.5A, 13A, 650mA         Power (Watts)       80W (110W Forced Air)         Applications       Medical         Voltage - Isolation       4kV (4000V)         Efficiency       75%         Operating Temperature       0°C ~ 50°C         Features       Universal Input         Mounting Type       Chassis Mount         Size / Dimension       6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Series	NLP110		
Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         5V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6.5A, 13A, 650mA           Power (Watts)         80W (110W Forced Air)           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         75%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Type	Open Frame		
Voltage - Output 1       12V         Voltage - Output 2       5V         Voltage - Output 3       -12V         Voltage - Output 4       -         Current - Output (Max)       6.5A, 13A, 650mA         Power (Watts)       80W (110W Forced Air)         Applications       Medical         Voltage - Isolation       4kV (4000V)         Efficiency       75%         Operating Temperature       0°C ~ 50°C         Features       Universal Input         Mounting Type       Chassis Mount         Size / Dimension       6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Number of Outputs	3		
Voltage - Output 2  Voltage - Output 3  -12V  Voltage - Output 4  -Current - Output (Max)  Power (Watts)  Applications  Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  O°C ~ 50°C  Features  Universal Input  Mounting Type  Size / Dimension  5V  -12V  -1	Voltage - Input	90 ~ 264 VAC		
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  O°C ~ 50°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - 12V  -	Voltage - Output 1	12V		
Voltage - Output 4       -         Current - Output (Max)       6.5A, 13A, 650mA         Power (Watts)       80W (110W Forced Air)         Applications       Medical         Voltage - Isolation       4kV (4000V)         Efficiency       75%         Operating Temperature       0°C ~ 50°C         Features       Universal Input         Mounting Type       Chassis Mount         Size / Dimension       6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Voltage - Output 2	5V		
Current - Output (Max) 6.5A, 13A, 650mA  Power (Watts) 80W (110W Forced Air)  Applications Medical  Voltage - Isolation 4kV (4000V)  Efficiency 75% Operating Temperature 0°C ~ 50°C  Features Universal Input  Mounting Type Chassis Mount Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Voltage - Output 3	-12V		
Power (Watts) 80W (110W Forced Air)  Applications Medical  Voltage - Isolation 4kV (4000V)  Efficiency 75%  Operating Temperature 0°C ~ 50°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation $4kV (4000V)$ Efficiency $75\%$ Operating Temperature $0^{\circ}C \sim 50^{\circ}C$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $6.50^{\circ}L \times 3.00^{\circ}W \times 1.26^{\circ}H (165.1mm \times 76.2mm \times 32.0mm)$	Current - Output (Max)	6.5A, 13A, 650mA		
Voltage - Isolation 4kV (4000V)  Efficiency 75%  Operating Temperature 0°C ~ 50°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Power (Watts)	80W (110W Forced Air)		
Efficiency 75%  Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Universal Input  Mounting Type Chassis Mount  Size / Dimension $6.50^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.26^{\circ}\text{H } (165.1\text{mm x } 76.2\text{mm x } 32.0\text{mm})$	Applications	Medical		
Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Universal Input  Mounting Type Chassis Mount  Size / Dimension $6.50^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.26^{\circ}\text{H } (165.1\text{mm x } 76.2\text{mm x } 32.0\text{mm})$	Voltage - Isolation	4kV (4000V)		
Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Efficiency	75%		
Mounting Type Chassis Mount Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Operating Temperature	0°C ~ 50°C		
Size / Dimension 6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)	Features	Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	6.50" L x 3.00" W x 1.26" H (165.1mm x 76.2mm x 32.0mm)		
		Report err	ors?	

### NLP110-9908 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **NLP110-9908 Payment Methods**



















# **NLP110-9908 Shipping Methods**













If you have any question about NLP110-9908, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com