

NLP25-7617 Information

Heisener.com

Part Number NLP25-7617

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 25W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP25-7617 Specifications

Manufacturer Part Number NLP25-7617 Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP25 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP25 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Manufacturer Part Number	NLP25-7617
Package - Series NLP25 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Manufacturer	Artesyn Embedded Technologies
Package - Series NLP25 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Category	Power Supplies - External/Internal (Off-Board)
Series NLP25 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Package	-
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)520mAPower (Watts)25WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 50°CFeaturesDC Input Capable, Universal InputMounting TypeChassis Mount	Series	NLP25
Voltage - Input90 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)520mAPower (Watts)25WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature0°C ~ 50°CFeaturesDC Input Capable, Universal InputMounting TypeChassis Mount	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sty (3000V) Efficiency Operating Temperature O°C ~ 50°C Features Mounting Type Voltage - Output 4 - Current - Output (Max) 520mA - Commercial) Sty (3000V) Efficiency O'C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency Operating Temperature O°C ~ 50°C Features Mounting Type Chassis Mount	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature O°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) 520mA Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Voltage - Output 2	-
Current - Output (Max) 520mA Power (Watts) 25W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Current - Output (Max)	520mA
Voltage - Isolation 3kV (3000V) Efficiency 70% Operating Temperature 0°C ~ 50°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Power (Watts)	25W
Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesDC Input Capable, Universal InputMounting TypeChassis Mount	Applications	ITE (Commercial)
Operating Temperature0°C ~ 50°CFeaturesDC Input Capable, Universal InputMounting TypeChassis Mount	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount	Efficiency	70%
Mounting Type Chassis Mount	Operating Temperature	0°C ~ 50°C
	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Size / Dimension 4.00" L x 2.07" W x 0.91" H (101.6mm x 52.6mm x 23.1mm)	Size / Dimension	4.00" L x 2.07" W x 0.91" H (101.6mm x 52.6mm x 23.1mm)
Report errors?		Report errors?

NLP25-7617 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP25-7617 Payment Methods


































If you have any question about NLP25-7617, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com