

NLP65-7610 Information



For Reference Only

Part Number NLP65-7610

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V +/-15V 65W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP65-7610 Specifications

Manufacturer Part Number NLP65-7610 Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP65-7610
Package - Series NLP65 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies
Package - Series NLP65 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series NLP65 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		AC DC Converters
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Package	-
Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Series	NLP65
Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 215VVoltage - Output 3-15VVoltage - Output 4-Current - Output (Max)7.5A, 2.2A, 850mAPower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°C (With Derating)FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 15V Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension 5V 15V 15V 15V 15V 15V 15V 15V	Number of Outputs	3
Voltage - Output 2 Voltage - Output 3 -15V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Size / Dimension 15V -15V -15V -15V -15V -15V -15V -15	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension Size / Dimension -15V -15V	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 2	15V
Current - Output (Max) 7.5A, 2.2A, 850mA Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 3	-15V
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Current - Output (Max)	7.5A, 2.2A, 850mA
Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Power (Watts)	65W (75W Forced Air)
Efficiency 72% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°C (With Derating)FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)
		Report errors?

NLP65-7610 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP65-7610 Payment Methods



















NLP65-7610 Shipping Methods













If you have any question about NLP65-7610, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com