

NLP65-7615G Information

For Reference Only

Part Number NLP65-7615G

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 65W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP65-7615G	Specifications
NLP03-/013(T	Specifications

Manufacturer Part Number NLP65-7615G Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP65-7615G
Package - Series NLP65 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies
Package - Series NLP65 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series NLP65 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Series	NLP65
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sity (3000V) Efficiency Operating Temperature Power (Wats) DC Input Capable, Universal Input Mounting Type Size / Dimension 15V 15V 15V 16V 15V 16V 16V 16V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Po°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - A.4A - Current - Output (Max) A.4A Fower (Watts) A5W (75W Forced Air) Air) A5W (3000V) Commercial) Commercial) Commercial) Commercial) Commercial) Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sity (3000V) Efficiency Operating Temperature DC Input Capable, Universal Input Mounting Type Size / Dimension - Current - Output (Max) 4.4A - Current - Output (Max) 4.4A Fower (Watts) Sity (75W Forced Air) ITE (Commercial) 3kV (3000V) Forced Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 4.4A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Universal Mount (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 2	-
Current - Output (Max) 4.4A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 65W (75W Forced Air) ITE (Commercial) 3kV (3000V) 72% Commercial) 10	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Current - Output (Max)	4.4A
Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Power (Watts)	65W (75W Forced Air)
Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Applications	ITE (Commercial)
Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Operating Temperature	0°C ~ 70°C
Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)
		Report errors?

NLP65-7615G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP65-7615G Payment Methods


































If you have any question about NLP65-7615G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com