

NLP65-7620 Information



For Reference Only

Part Number NLP65-7620

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 24V 65W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP65-7620 Specifications

Manufacturer Part Number NLP65-7620 Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP65-7620
Package - Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies
Package - Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		AC DC Converters
TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Package	-
Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Series	NLP65
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension 5 V Voltage - Output 2 24V 24V 24V 24V 24V 24V - 24V	Number of Outputs	2
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension 24V 24V 24V 24V 24V Chassis Mount - Current - Output (Anx) 7A, 2A 65W (75W Forced Air) ITE (Commercial) 8kV (3000V) Commercial) 72% Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Size / Dimension - Output 4 - Chassis Mount - Chassis Mount Size / Dimension - Output 4 - Chassis Mount - Chassis Mount	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 2	24V
Current - Output (Max) Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7A, 2A 65W (75W Forced Air) ITE (Commercial) SkV (3000V) Commercial) About (3000V) Commercial) SkV (3000V) Commercial) About (3000V) Commercial) SkV (3000V) Commercial) Commercial) SkV (3000V) Commercial) SkV (3000V) Commercial) SkV (3000V) Commercial) Commercial Commercial) Commercial Comm	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 72% Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension 5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2 mm x 32.0 mm)	Current - Output (Max)	7A, 2A
Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Power (Watts)	65W (75W Forced Air)
Efficiency 72% Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.26^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 32.0\text{mm})$	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Operating Temperature	0°C ~ 70°C
Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)
		Report errors?

NLP65-7620 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP65-7620 Payment Methods





















NLP65-7620 Shipping Methods













If you have any question about NLP65-7620, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com