

NLP65-7620

NLP65-7620 Information

	Part Number Manufacturer Category Description Package	Artesyn Embedded Technologies Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 5V 24V 65W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



NLP65-7620 Specifications

Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters AC DC Converters Package - Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chasis Mount Size / Dimension 5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP65-7620	
AC DC ConvertersPackage-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output 4-Power (Watts)65W (75W Forced Air)Voltage - Isolation3kV (300V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies	
Package-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 45W (75W Forced Air)Power (Wats)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency0°C ~ 70°CPeaturesDC Input Capable, Universal InputMounting TypeChasis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series NLP65 Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Voltage - Isolation XV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chasis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		AC DC Converters	
Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 65W (75W Forced Air) Power (Watts) AV (3000V) Poltications 3kV (3000V) Efficiency 0°C ~ 70°C Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)	Package	-	
Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Series	NLP65	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7A, 2A Power (Watts) 65W (75W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature 0°C ~ 70°C Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Туре	Open Frame	
Voltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (commercial)Voltage - Isolation3kV (3000V)Efficiency0°C ~ 70°CPoatrentsDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Number of Outputs	2	
Voltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 1	5V	
Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 2	24V	
Current - Output (Max)7A, 2APower (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 3	-	
Power (Watts)65W (75W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Current - Output (Max)	7A, 2A	
Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Power (Watts)	65W (75W Forced Air)	
Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Applications	ITE (Commercial)	
Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Isolation	3kV (3000V)	
FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Efficiency	72%	
Mounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Operating Temperature	$0^{\circ}C \sim 70^{\circ}C$	
Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Features	DC Input Capable, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	
*			Report errors?

NLP65-7620 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP65-7620 Payment Methods \swarrow WIRE transfer PayPal PayPal

If you have any question about NLP65-7620, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com