

## NLP65-9620J

#### NLP65-9620J Information

	Part Number Manufacturer Category Description Package	Artesyn Embedded Technologies Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 5V 24V 60W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## NLP65-9620J Specifications

Manufacturer Artesyn Embedded Technologies   Power Supplies - External/Internal (Off-Board) AC DC Converters   Package -   Series NLP65   Syries Specification   Number of Outputs Open Frame   Voltage - Input Soft - 264 VAC   Voltage - Output 1 Sv   Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Output 5 -   Voltage - Output 6 -   Voltage - Output 7 -   Voltage - Output 8 -   Voltage - Output 9 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Output 6 -   Voltage - Solation Applications   Applications TE (Commercial)   Voltage - Isolation SV (3000V)   Efficiency 72%   Operating Temperature OC AppleL, Universal Input   Features DinutGapable, Universal Input			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)	Manufacturer Part Number	NLP65-9620J	
AC DC ConvertersPackage-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output 4-Power (Watts)60W (70W Forced Air)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00° L x 3.00° W x 1.26° H (127.0mm x 76.2mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies	
Package-SeriesNLP65TypeOpen FrameNumber of Outputs2Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 460W (70W Forced Air)Power (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency0°C ~ 70°CPeaturesDC Input Capable, Universal InputMounting TypeChasis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series NLP65   Type Open Frame   Number of Outputs 2   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 7A, 2A   Power (Watts) 60W (70W Forced Air)   Voltage - Isolation 3kV (3000V)   Efficiency 72%   Operating Temperature 0°C ~ 70°C   Features DC Input Capable, Universal Input   Mounting Type Chasis Mount   Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)		AC DC Converters	
Type Open Frame   Number of Outputs 2   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 5 60W (70W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 72%   Operating Temperature 0°C ~ 70°C   Features DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Package	-	
Number of Outputs 2   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 7A, 2A   Power (Watts) 60W (70W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 72%   Operating Temperature 0°C ~ 70°C   Features DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Series	NLP65	
Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 7A, 2A   Power (Watts) 60W (70W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 72%   Operating Temperature 0°C ~ 70°C   Features DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Туре	Open Frame	
Voltage - Output 15VVoltage - Output 224VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)60W (70W Forced Air)ApplicationsITE (commercial)Voltage - Isolation3kV (3000V)Efficiency0°C ~ 70°CPoatrentsDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Number of Outputs	2	
Voltage - Output 2 24V   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 7A, 2A   Power (Watts) 60W (70W Forced Air)   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 72%   Operating Temperature 0°C ~ 70°C   Features DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting Type5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 1	5V	
Voltage - Output 4-Current - Output (Max)7A, 2APower (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 2	24V	
Current - Output (Max)7A, 2APower (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 3	-	
Power (Watts)60W (70W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Current - Output (Max)	7A, 2A	
Voltage - Isolation3kV (3000V)Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Power (Watts)	60W (70W Forced Air)	
Efficiency72%Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Applications	ITE (Commercial)	
Operating Temperature0°C ~ 70°CFeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Voltage - Isolation	3kV (3000V)	
FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Efficiency	72%	
Mounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Operating Temperature	$0^{\circ}C \sim 70^{\circ}C$	
Size / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	Features	DC Input Capable, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	ze / Dimension 5.00" L x 3.00" W x 1.26" H (127.0mm x 76.2mm x 32.0mm)	
			Report errors?

#### NLP65-9620J Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### NLP65-9620J Payment Methods



### NLP65-9620J Shipping Methods



If you have any question about NLP65-9620J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com