

# NLS-1-BK-C185-M40S

#### NLS-1-BK-C185-M40S Information

Heisener.com	 NLS-1-BK-C185-M40S ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN LINE SOURCE CRIMP 1POS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## NLS-1-BK-C185-M40S Specifications

Manufacturer Part Number NLS-1-BK-C185-M40S   Manufacturer IT Cannon, LLC   Category Connectors, Interconnects   Package -   Package -   Series Powerlock   Connector Type Line Source, Male Pins   Number of Positions 1   Shell Size - Insert -   Mounting Type Free Hanging (In-Line)   Termination Crimp   Fastening Type Bayonet Lock   Orientation Keyed   Ingress Protection Infernoplastic   Shell Material, Finish Thermoplastic   Contact Finish Silver   Features -   Voltage - Rated 1000VAC, 1500VDC		
CategoryConnectors, InterconnectsCarcular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpIngress ProtectionBayonet LockIngress ProtectionStell SizeShell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer Part Number	NLS-1-BK-C185-M40S
PackageCircular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionThermoplasticShell Material, FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationHofer Jourge J	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationHoff - Dust Tight, WaterproofIngress ProtectionSilverShell Material, FinishSilverFoatteres-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverFortaresSilverVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Package	-
Number of Positions1Number of Positions-Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionNerroplasticShell Material, FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Connector Type	Line Source, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionMontantiger SpaceShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Termination	Crimp
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Orientation	Keyed
Contact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Material, Finish	Thermoplastic
Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Contact Finish	Silver
Current Rating 660A	Features	-
	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

#### NLS-1-BK-C185-M40S Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### NLS-1-BK-C185-M40S Payment Methods



### NLS-1-BK-C185-M40S Shipping Methods



If you have any question about NLS-1-BK-C185-M40S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com