

NLS-2-W-S120-M40B

NLS-2-W-S120-M40B Information

Contail lervice stands been	 NLS-2-W-S120-M40B ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN LINE SOURCE SET SCREW 1POS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



NLS-2-W-S120-M40B Specifications

ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDC		
CategoryConnectors, InterconnectsCarcular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewPastening TypeBayonet LockOrientationIP67 - Dust Tight, WaterproofShell Material, FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Manufacturer Part Number	NLS-2-W-S120-M40B
Circular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress Protection1hermoplasticShell Material, FinishThermoplasticContact Finish-Features-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionFiler Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverVoltage - Rated1000VAC, 1500VDCCurrent Rating400A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionThermoplasticShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A		Circular Connectors
Connector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionPfo7 - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverFastening-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Series	Powerlock
Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Connector Type	Line Source, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCKent Material, Silver400A	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCKent Material400A	Shell Size - Insert	-
TerminationSet ScrewFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Termination	Set Screw
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Orientation	Keyed
Contact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features-Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Shell Material, Finish	Thermoplastic
Voltage - Rated1000VAC, 1500VDCCurrent Rating400A	Contact Finish	Silver
Current Rating 400A	Features	-
-	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	400A
		Report errors?

NLS-2-W-S120-M40B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

NLS-2-W-S120-M40B Payment Methods





If you have any question about NLS-2-W-S120-M40B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com