

NLS-3-GY-C300-M50-HG Information

Heisener.com

Part Number NLS-3-GY-C300-M50-HG

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

CONN LINE SOURCE CRIMP 1POS **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLS-3-GY-C300-M50-HG Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package Powerlock Connector Type Line Source, Male Pins Number of Positions I Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating Connector SHE Connectors Circular Connectors Connector Shell Materials ITT Cannon, LLC Connectors Iteroconnector Iteroco		
Category Connectors, Interconnects Circular Connectors Package - Series Powerlock Connector Type Line Source, Male Pins Number of Positions I Shell Size - Insert Shell Size, MIL Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated Current Rating Circular Connectors Connectors Line Source, Male Pins Line Source, Male Source, Male Source, Male Source, Male Source, Male Source, M	Manufacturer Part Number	NLS-3-GY-C300-M50-HG
Circular Connectors Package - Series Powerlock Connector Type Line Source, Male Pins Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Manufacturer	ITT Cannon, LLC
Package - Series Powerlock Connector Type Line Source, Male Pins Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesHand GripVoltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector Type Line Source, Male Pins Number of Positions 1 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Package	-
Number of Positions Shell Size - Insert - Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Series	Powerlock
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Connector Type	Line Source, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating Free Hanging (In-Line)	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeaturesHand GripVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Thermoplastic Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Orientation	Keyed
Contact Finish Silver Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Hand Grip Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Contact Finish	Silver
Current Rating 660A	Features	Hand Grip
	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

NLS-3-GY-C300-M50-HG Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLS-3-GY-C300-M50-HG Payment Methods



















NLS-3-GY-C300-M50-HG Shipping Methods













If you have any question about NLS-3-GY-C300-M50-HG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com