



Heisener.com

NLS-E-GN-C120-M40A Information

Part Number NLS-E-GN-C120-M40A

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN LINE SOURCE CRIMP 1POS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLS-E-GN-C120-M40A Specifications

Manufacturer Part NumberNLS-E-GN-C120-M40AManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer Part Number	NLS-E-GN-C120-M40A
Package-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Connector Type	Line Source, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating -	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating Bayonet Lock Reyed IP67 - Dust Tight, Waterproof Thermoplastic 1000VAC, 1500VDC	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Thermoplastic 1000VAC, 1500VDC 660A	Orientation	Keyed
Contact Finish Silver Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Shell Material, Finish	Thermoplastic
Voltage - Rated 1000VAC, 1500VDC Current Rating 660A	Contact Finish	Silver
Current Rating 660A	Features	-
-	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

NLS-E-GN-C120-M40A Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLS-E-GN-C120-M40A Payment Methods



















NLS-E-GN-C120-M40A Shipping Methods













If you have any question about NLS-E-GN-C120-M40A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com