

NLS-N-BK-C150-M40A

NLS-N-BK-C150-M40A Information

Heisener.com	NLS-N-BK-C150-M40A ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN LINE SOURCE CRIMP 1POS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



NLS-N-BK-C150-M40A Specifications

Manufacturer ITT Cannon, LLC Connectors, Interconnects Circular Connectors Package - Package - Series Powerlock Connector Type Line Source, Male Pins Number of Positions 1 Shell Size - Insert - Mounting Type - Mounting Type Free Hanging (In-Line) Packaging Keyed Ingress Protection Keyed Interroplattic Silver Shell Material, Finish Thermoplastic Contact Finish Silver Features - Contact Finish GiovAC, 1500VDC Current Rating GiovAC, 1500VDC		
CategoryConnectors, InterconnectsCarcular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationHeroplasticShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer Part Number	NLS-N-BK-C150-M40A
Circular ConnectorsPackage-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress Protection1hermoplasticShell Material, FinishThermoplasticContact Finish-Features-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Manufacturer	ITT Cannon, LLC
Package-SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeBayonet LockPastening TypeBayonet LockOrientationIP67 - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverVoltage - Rated1000VAC, 1500VDCCurrent Rating660A	Category	Connectors, Interconnects
SeriesPowerlockConnector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationHP67 - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A		Circular Connectors
Connector TypeLine Source, Male PinsNumber of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionNemoplasticShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Package	-
Number of Positions1Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Series	Powerlock
Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Connector Type	Line Source, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Number of Positions	1
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCKender660A	Shell Size - Insert	-
TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Termination	Crimp
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Orientation	Keyed
Contact FinishSilverFeatures-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features-Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Shell Material, Finish	Thermoplastic
Voltage - Rated1000VAC, 1500VDCCurrent Rating660A	Contact Finish	Silver
Current Rating 660A	Features	-
-	Voltage - Rated	1000VAC, 1500VDC
Report errors?	Current Rating	660A
		Report errors?

NLS-N-BK-C150-M40A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

NLS-N-BK-C150-M40A Payment Methods



NLS-N-BK-C150-M40A Shipping Methods



If you have any question about NLS-N-BK-C150-M40A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com