



### NM27C040V200 Information

Heisener com

Part Number NM27C040V200

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)

Memory

**Description** IC EPROM 4M PARALLEL 32PLCC

Package 32-LCC (J-Lead)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## NM27C040V200 Specifications

Manufacturer Part Number         NM27C040V200           Manufacturer         ON Semiconductor           Category         Integrated Circuits (ICs)           Memory         Memory           Package         32-LCC (J-Lead)           Series         -           Memory Type         Non-Volatile           Memory Format         EPROM           Technology         EPROM - OTP           Memory Size         4Mb (512K x 8)           Memory Interface         Parallel           Clock Frequency         -           Write Cycle Time - Word, Page         -           Access Time         200ns           Voltage - Supply         4.5 V ~ 5.5 V           Operating Temperature         0°C ~ 70°C (TA)           Mounting Type         Surface Mount           Package / Case         32-LCC (J-Lead)           Supplier Device Package         32-PLCC (14x11.46)	•	
Category         Integrated Circuits (ICs)           Memory           Package         32-LCC (J-Lead)           Series         -           Memory Type         Non-Volatile           Memory Format         EPROM           Technology         EPROM - OTP           Memory Size         4Mb (512K x 8)           Memory Interface         Parallel           Clock Frequency         -           Write Cycle Time - Word, Page         -           Access Time         200ns           Voltage - Supply         4.5 V ~ 5.5 V           Operating Temperature         0°C ~ 70°C (TA)           Mounting Type         Surface Mount           Package / Case         32-LCC (J-Lead)           Supplier Device Package         32-PLCC (14x11.46)	Manufacturer Part Number	NM27C040V200
Memory         Package       32-LCC (J-Lead)         Series       -         Memory Type       Non-Volatile         Memory Format       EPROM         Technology       EPROM - OTP         Memory Size       4Mb (512K x 8)         Memory Interface       Parallel         Clock Frequency       -         Write Cycle Time - Word, Page       -         Access Time       200ns         Voltage - Supply       4.5 V ~ 5.5 V         Operating Temperature       0°C ~ 70°C (TA)         Mounting Type       Surface Mount         Package / Case       32-LCC (J-Lead)         Supplier Device Package       32-PLCC (14x11.46)	Manufacturer	ON Semiconductor
Package32-LCC (J-Lead)Series-Memory TypeNon-VolatileMemory FormatEPROMTechnologyEPROM - OTPMemory Size4Mb (512K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time200nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)Supplier Device Package32-PLCC (14x11.46)	Category	Integrated Circuits (ICs)
Series - Memory Type Non-Volatile  Memory Format EPROM  Technology EPROM - OTP  Memory Size 4Mb (512K x 8)  Memory Interface Parallel  Clock Frequency - Write Cycle Time - Word, Page - Supply 4.5 V ~ 5.5 V  Operating Temperature 0°C ~ 70°C (TA)  Mounting Type Surface Mount  Package / Case 32-LCC (J-Lead)  Supplier Device Package 32-PLCC (14x11.46)		Memory
Memory TypeNon-VolatileMemory FormatEPROMTechnologyEPROM - OTPMemory Size4Mb (512K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time200nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)Supplier Device Package32-PLCC (14x11.46)	Package	32-LCC (J-Lead)
Memory FormatEPROMTechnologyEPROM - OTPMemory Size4Mb (512K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time200nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)Supplier Device Package32-PLCC (14x11.46)	Series	-
Technology  Memory Size  4Mb (512K x 8)  Memory Interface  Parallel  Clock Frequency  - Write Cycle Time - Word, Page  Access Time  200ns  Voltage - Supply  Operating Temperature  Mounting Type  Surface Mount  Package / Case  Supplier Device Package  EPROM - OTP  4Mb (512K x 8)  Parallel  - Clock Frequency  - 0° 0° 0° 0° 0° 0° 0° 0° 0° 0° 0° 0° 0°	Memory Type	Non-Volatile
Memory Size4Mb (512K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time200nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)Supplier Device Package32-PLCC (14x11.46)	Memory Format	EPROM
Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time200nsVoltage - Supply4.5 V ~ 5.5 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)Supplier Device Package32-PLCC (14x11.46)	Technology	EPROM - OTP
Clock Frequency  Write Cycle Time - Word, Page  Access Time  200ns  Voltage - Supply  4.5 V ~ 5.5 V  Operating Temperature  0°C ~ 70°C (TA)  Mounting Type  Surface Mount  Package / Case  32-LCC (J-Lead)  Supplier Device Package	Memory Size	4Mb (512K x 8)
Write Cycle Time - Word, Page  Access Time  200ns  Voltage - Supply  4.5 V ~ 5.5 V  Operating Temperature  0°C ~ 70°C (TA)  Mounting Type  Surface Mount  Package / Case  32-LCC (J-Lead)  Supplier Device Package	Memory Interface	Parallel
Access Time $200 \text{ns}$ Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (TA)Mounting TypeSurface MountPackage / Case $32\text{-LCC}$ (J-Lead)Supplier Device Package $32\text{-PLCC}$ (14x11.46)	Clock Frequency	-
Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (TA)Mounting TypeSurface MountPackage / Case $32\text{-LCC}$ (J-Lead)Supplier Device Package $32\text{-PLCC}$ ( $14x11.46$ )	Write Cycle Time - Word, Page	-
Operating Temperature  0°C ~ 70°C (TA)  Mounting Type  Surface Mount  Package / Case  32-LCC (J-Lead)  Supplier Device Package  32-PLCC (14x11.46)	Access Time	200ns
Mounting Type Surface Mount Package / Case 32-LCC (J-Lead) Supplier Device Package 32-PLCC (14x11.46)	Voltage - Supply	4.5 V ~ 5.5 V
Package / Case 32-LCC (J-Lead) Supplier Device Package 32-PLCC (14x11.46)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C} \text{ (TA)}$
Supplier Device Package 32-PLCC (14x11.46)	Mounting Type	Surface Mount
	Package / Case	32-LCC (J-Lead)
	Supplier Device Package	32-PLCC (14x11.46)
Report errors?		Report errors?

#### NM27C040V200 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## NM27C040V200 Payment Methods



















## NM27C040V200 Shipping Methods













If you have any question about NM27C040V200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com