



NND151212 Information



For Reference Only

Part Number NND151212

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 18W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NND151212 Specifications

Manufacturer Part Number NND151212 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NN Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NN Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Manufacturer Part Number	NND151212	
Package - Series NN Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series NN Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series NN Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)		AC DC Converters	
Type Open Frame Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Package	-	
Number of Outputs 2 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Series	NN	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Type	Open Frame	
Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 12V -12V -12	Number of Outputs	2	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency Operating Temperature Features Universal Input Mounting Type Chassis Mount Size / Dimension -12V -12V -12V -12V -12V -12V -12V -12	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Universal Size / Dimension - Current - Output (Max) - Commercial (M	Voltage - Output 1	12V	
Voltage - Output 4 Current - Output (Max) 750mA, 750mA Power (Watts) 18W Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Voltage - Output 2	-12V	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 750mA, 750mA 750mA 750mA 750mA 750mA 750mA 750mA 18W Applications 17E (Commercial) 3.75kV (3750V) 45% Cyperating Temperature -20°C ~ 71°C (With Derating) Universal Input Chassis Mount 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 18W 18W 18W 18W 18W 18W 18W 1980 1990 45% Commercial) 1900	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Current - Output (Max)	750mA, 750mA	
Voltage - Isolation 3.75kV (3750V) Efficiency 45% Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Power (Watts)	18W	
Efficiency 45% Operating Temperature $-20^{\circ}\text{C} \sim 71^{\circ}\text{C}$ (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension $5.91^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 4.47^{\circ}\text{H}$ (150.0mm x 60.0mm x 113.5mm)	Applications	ITE (Commercial)	
Operating Temperature -20°C ~ 71°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Voltage - Isolation	3.75kV (3750V)	
Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Efficiency	45%	
Mounting Type Chassis Mount Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Operating Temperature	-20°C ~ 71°C (With Derating)	
Size / Dimension 5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	Features	Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.91" L x 2.36" W x 4.47" H (150.0mm x 60.0mm x 113.5mm)	
		Report errors	?

NND151212 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NND151212 Payment Methods



















NND151212 Shipping Methods













If you have any question about NND151212, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com