

#### NPC-1220-030A3S Information



For Reference Only

Part Number NPC-1220-030A3S

Manufacturer Amphenol Advanced Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESS SENS 0 TO 30PSI ABSLTE

Package 8-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## NPC-1220-030A3S Specifications

Manufacturer       NPC-1220-030A3S         Manufacturer       Amphenol Advanced Sensors         Category       Sensors, Transducers         Package       8-DIP Module         Series       NPC-1220         Pressure Type       Absolute         Operating Pressure       30 PSI (206.84 kPa)         Output Type       Wheatstone Bridge         Output       0 mV ~ 50 mV         Accuracy       ±0.1%         Voltage - Supply       -         Port Size       Male - 0.12" (3.04mm) Tube         Port Style       Barbless         Features       Temperature Compensated         Termination Style       PCB         Maximum Pressure       90 PSI (620.53 kPa)         Operating Temperature       -40°C ~ 125°C         Package / Case       8-DIP Module         Supplier Device Package       -		
Category         Sensors, Transducers           Package         8-DIP Module           Series         NPC-1220           Pressure Type         Absolute           Operating Pressure         30 PSI (206.84 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 50 mV           Accuracy         ±0.1%           Voltage - Supply         -           Port Size         Male - 0.12" (3.04mm) Tube           Port Style         Barbless           Features         Temperature Compensated           Termination Style         PCB           Maximum Pressure         90 PSI (620.53 kPa)           Operating Temperature         -40°C ~ 125°C           Package / Case         8-DIP Module           Supplier Device Package         -	Manufacturer Part Number	NPC-1220-030A3S
Package 8-DIP Module Series NPC-1220 Pressure Type Absolute Operating Pressure Operating Pressure Output Type Wheatstone Bridge Output Output Quality	Manufacturer	Amphenol Advanced Sensors
Package         8-DIP Module           Series         NPC-1220           Pressure Type         Absolute           Operating Pressure         30 PSI (206.84 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 50 mV           Accuracy         ±0.1%           Voltage - Supply         -           Port Size         Male - 0.12" (3.04mm) Tube           Port Style         Barbless           Features         Temperature Compensated           Termination Style         PCB           Maximum Pressure         90 PSI (620.53 kPa)           Operating Temperature         -40°C ~ 125°C           Package / Case         8-DIP Module           Supplier Device Package         -	Category	Sensors, Transducers
SeriesNPC-1220Pressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 50 mVAccuracy±0.1%Voltage - Supply-Port SizeMale - 0.12" (3.04mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure90 PSI (620.53 kPa)Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 50 mVAccuracy±0.1%Voltage - Supply-Port SizeMale - 0.12" (3.04mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure90 PSI (620.53 kPa)Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-	Package	8-DIP Module
Operating Pressure Output Type Wheatstone Bridge Output Ou	Series	NPC-1220
Output TypeWheatstone BridgeOutput0 mV ~ 50 mVAccuracy±0.1%Voltage - Supply-Port SizeMale - 0.12" (3.04mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure90 PSI (620.53 kPa)Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-	Pressure Type	Absolute
Output 0 mV ~ 50 mV  Accuracy ±0.1%  Voltage - Supply -  Port Size Male - 0.12" (3.04mm) Tube  Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 90 PSI (620.53 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 8-DIP Module  Supplier Device Package	Operating Pressure	30 PSI (206.84 kPa)
Accuracy ±0.1%  Voltage - Supply -  Port Size Male - 0.12" (3.04mm) Tube  Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 90 PSI (620.53 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 8-DIP Module  Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply  Port Size  Male - 0.12" (3.04mm) Tube  Barbless  Features  Temperature Compensated  Termination Style  Maximum Pressure  90 PSI (620.53 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  8-DIP Module  Supplier Device Package	Output	0 mV ~ 50 mV
Port Size Male - 0.12" (3.04mm) Tube  Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 90 PSI (620.53 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 8-DIP Module  Supplier Device Package -	Accuracy	±0.1%
Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 90 PSI (620.53 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 8-DIP Module  Supplier Device Package	Voltage - Supply	-
FeaturesTemperature CompensatedTermination StylePCBMaximum Pressure90 PSI (620.53 kPa)Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-	Port Size	Male - 0.12" (3.04mm) Tube
Termination Style PCB  Maximum Pressure 90 PSI (620.53 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 8-DIP Module  Supplier Device Package -	Port Style	Barbless
Maximum Pressure90 PSI (620.53 kPa)Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / Case8-DIP ModuleSupplier Device Package-	Termination Style	PCB
Package / Case 8-DIP Module Supplier Device Package -	Maximum Pressure	90 PSI (620.53 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	8-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

#### NPC-1220-030A3S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### NPC-1220-030A3S Payment Methods



















## NPC-1220-030A3S Shipping Methods













If you have any question about NPC-1220-030A3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com