



NPI-15A-3K0SV Information

elsener.com

For Reference Only

Part Number NPI-15A-3K0SV

Manufacturer Amphenol Advanced Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 3KPSI SEALED GAUGE

Package Cylinde

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NPI-15A-3K0SV Specifications

Manufacturer Part Number NPI-15A-3K0SV Manufacturer Amphenol Advanced Sensors Category Sensors, Transducers Package Cylinder Series NPI-15VC Pressure Type Sealed Gauge Operating Pressure 3000 PSI (20684.27 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.35% Voltage - Supply 10 V ~ 15 V Port Size - Port Style No Port Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinderSeriesNPI-15VCPressure TypeSealed GaugeOperating Pressure3000 PSI (20684.27 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.35%Voltage - Supply10 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	NPI-15A-3K0SV
Package Cylinder Series NPI-15VC Pressure Type Sealed Gauge Operating Pressure Output Type Wheatstone Bridge Output (10V) Accuracy ±0.35% Voltage - Supply 10 V ~ 15 V Port Size - Port Style No Port Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Manufacturer	Amphenol Advanced Sensors
PackageCylinderSeriesNPI-15VCPressure TypeSealed GaugeOperating Pressure3000 PSI (20684.27 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.35%Voltage - Supply10 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesNPI-15VCPressure TypeSealed GaugeOperating Pressure3000 PSI (20684.27 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.35%Voltage - Supply10 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 3000 PSI (20684.27 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.35% Voltage - Supply 10 V ~ 15 V Port Size - Port Style No Port Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Package	Cylinder
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 100 mV (10V) Accuracy ±0.35% Voltage - Supply In V ~ 15 V Port Size - Port Style No Port Features Temperature Compensated Termination Style Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - Cutput Subbasiana Subbas	Series	NPI-15VC
Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.35%Voltage - Supply10 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output $0 \text{ mV} \sim 100 \text{ mV} (10\text{V})$ Accuracy $\pm 0.35\%$ Voltage - Supply $10 \text{ V} \sim 15 \text{ V}$ Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure $6000 \text{ PSI } (41368.54 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	3000 PSI (20684.27 kPa)
Accuracy $\pm 0.35\%$ Voltage - Supply $10 \text{ V} \sim 15 \text{ V}$ Port Size - Port Style No Port Features Temperature Compensated Termination Style Flex Cable Maximum Pressure $6000 \text{ PSI } (41368.54 \text{ kPa})$ Operating Temperature - $40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply Port Size - Port Style No Port Features Temperature Compensated Termination Style Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 10 V ~ 15 V 6000 Port An Operating Temperature Compensated Flex Cable Cylinder -40°C ~ 125°C Cylinder -40°C ~ 125°C	Output	$0 \text{ mV} \sim 100 \text{ mV} (10 \text{V})$
Port Size - No Port Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.35%
Port Style Features Temperature Compensated Termination Style Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Voltage - Supply	10 V ~ 15 V
Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Size	-
Termination Style Flex Cable Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Style	No Port
Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Features	Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Flex Cable
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	6000 PSI (41368.54 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
_		Report errors?

NPI-15A-3K0SV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NPI-15A-3K0SV Payment Methods



















NPI-15A-3K0SV Shipping Methods













If you have any question about NPI-15A-3K0SV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com