



NPI-19H-201GH Information

Part Number NPI-19H-201GH

Manufacturer Amphenol Advanced Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 29PSI GAUGE

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NPI-19H-201GH Specifications

Manufacturer Part Number NPI-19H-201GH Manufacturer Amphenol Advanced Sensors Category Sensors, Transducers Package Cylinder Series NPI-19 Pressure Type Vented Gauge Operating Pressure 29.01 PSI (200 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesNPI-19Pressure TypeVented GaugeOperating Pressure29.01 PSI (200 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	NPI-19H-201GH
Package Cylinder Series NPI-19 Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure Operating Temperature - 40°C ~ 125°C Package / Case Supplier Device Package Pressure Supline Cylinder Cylinder Cylinder Polit Sensors, Transducers NPI-19 Polit Gensors, Transducers NPI-19 Polit Gauge Vented Gauge 1 mel (6.35mm) NPT Threaded Flex Cable Flex Cable Assimum Pressure Compensated Flex Cable Supplier Device Package	Manufacturer	Amphenol Advanced Sensors
Package Cylinder Series NPI-19 Pressure Type Vented Gauge Operating Pressure 29.01 PSI (200 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Category	Sensors, Transducers
SeriesNPI-19Pressure TypeVented GaugeOperating Pressure29.01 PSI (200 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure29.01 PSI (200 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Maximum Pressure Seatores Features Fex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - Cylinder	Series	NPI-19
Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleFlex CableMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Vented Gauge
Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Operating Pressure	29.01 PSI (200 kPa)
Accuracy ±0.25% Voltage - Supply - Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Output	$0 \text{ mV} \sim 100 \text{ mV}$
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	-
Features Temperature Compensated Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Flex Cable Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Features	Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Flex Cable
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	58.02 PSI (400 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
I.		Report errors?

NPI-19H-201GH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NPI-19H-201GH Payment Methods



















NPI-19H-201GH Shipping Methods













If you have any question about NPI-19H-201GH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com