

NPPN032AFEN-RC

NPPN032AFEN-RC Information

Heisener.com

For Reference Only

Part Number NPPN032AFEN-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN HEADER .079" 6POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NPPN032AFEN-RC Specifications

Manufacturer Part Number NPPN032AFEN-RC Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Testening Type Through Hole Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C Material Flammability Rating UL94 V-0				
Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	NPPN032AFEN-RC		
Package-Series-Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Sullins Connector Solutions		
Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects		
Series-Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Package	-		
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Series	-		
StyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Connector Type	Header		
Number of Positions Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket		
Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Style	Board to Board		
Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Number of Positions	6		
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.169" (4.30mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All		
Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.169" (4.30mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Pitch - Mating	0.079" (2.00mm)		
Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Number of Rows	2		
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	0.079" (2.00mm)		
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole		
Contact Finish - Mating Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Termination	Solder		
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.169" (4.30mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height $0.169"$ (4.30mm)Contact Length - Post $0.110"$ (2.79mm)Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish - Mating	Gold		
Insulation Height $0.169" (4.30 \text{mm})$ Contact Length - Post $0.110" (2.79 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash		
Contact Length - Post $0.110" (2.79 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black		
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.169" (4.30mm)		
	Contact Length - Post	0.110" (2.79mm)		
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C		
	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Gold		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

NPPN032AFEN-RC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NPPN032AFEN-RC Payment Methods





















NPPN032AFEN-RC Shipping Methods













If you have any question about NPPN032AFEN-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com