

## NPPN091BFCN-RC

#### NPPN091BFCN-RC Information

Part Number NPPN091BFCN-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** CONN RECEPT 2MM SINGLE STR 9POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## NPPN091BFCN-RC Specifications

Manufacturer Part Number         NPPN091BFCN-RC           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.173" (4.40mm)           Contact Length - Post         0.094" (2.40mm)           Operating Temperature         -40°C ~ 105°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.173" (4.40mm)           Contact Length - Post         0.094" (2.40mm)           Operating Temperature         -40°C ~ 105°C	Manufacturer Part Number	NPPN091BFCN-RC
Package-Series-Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions9Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.173" (4.40mm)           Contact Length - Post         0.094" (2.40mm)           Operating Temperature         -40°C ~ 105°C	Category	Connectors, Interconnects
Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.173" (4.40mm)           Contact Length - Post         0.094" (2.40mm)           Operating Temperature         -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions9Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions9Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Series	-
StyleBoard to BoardNumber of Positions9Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Connector Type	Header
Number of Positions 9 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.094" (2.40mm) Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Style	Board to Board
Pitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.094" (2.40mm)Operating Temperature-40°C ~ 105°C	Number of Positions	9
Number of Rows Row Spacing - Mating	Number of Positions Loaded	All
Row Spacing - Mating  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.173" (4.40mm)  Contact Length - Post  0.094" (2.40mm)  Operating Temperature  -40°C ~ 105°C	Pitch - Mating	0.079" (2.00mm)
Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.173" (4.40mm)  Contact Length - Post 0.094" (2.40mm)  Operating Temperature -40°C ~ 105°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.094" (2.40mm) Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	-
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.173" (4.40mm)  Contact Length - Post 0.094" (2.40mm)  Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.094" (2.40mm) Operating Temperature -40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.094" (2.40mm) Operating Temperature -40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.173"$ (4.40mm)Contact Length - Post $0.094"$ (2.40mm)Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.173"$ (4.40mm)Contact Length - Post $0.094"$ (2.40mm)Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash
Contact Length - Post $0.094" (2.40mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.173" (4.40mm)
	Contact Length - Post	0.094" (2.40mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### NPPN091BFCN-RC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### NPPN091BFCN-RC Payment Methods

































If you have any question about NPPN091BFCN-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com