

## NPRN234EFCN-RC

### **NPRN234EFCN-RC Information**

Heisener.com

For Reference Only

Part Number NPRN234EFCN-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** CONN HEADER .079" 92POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# NPRN234EFCN-RC Specifications

Manufacturer Part NumberNPRN234EFCN-RCManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Series-Connector TypeHeaderContact TypeForkedStyleBoard to BoardNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolder		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series - Connector Type Header Contact Type Forked Style Board to Board Number of Positions  Number of Positions Loaded Pitch - Mating Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole	Manufacturer Part Number	NPRN234EFCN-RC
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series - Connector Type Header Contact Type Forked Style Board to Board Number of Positions 92 Number of Positions Loaded Pitch - Mating Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole	Manufacturer	Sullins Connector Solutions
Package - Series - Connector Type Header Contact Type Forked Style Board to Board Number of Positions 92 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole	Category	Connectors, Interconnects
Series - Connector Type Header Contact Type Forked Style Board to Board Number of Positions 92 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Header  Contact Type Forked  Style Board to Board  Number of Positions 92  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 4  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole	Package	-
Contact Type Forked  Style Board to Board  Number of Positions 92  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 4  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole	Series	-
StyleBoard to BoardNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole	Connector Type	Header
Number of Positions 92  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 4  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole	Contact Type	Forked
Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole	Style	Board to Board
Pitch - Mating 0.079" (2.00mm)  Number of Rows 4  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole	Number of Positions	92
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole	Number of Positions Loaded	All
Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole	Pitch - Mating	0.079" (2.00mm)
Mounting Type Through Hole	Number of Rows	4
	Row Spacing - Mating	0.079" (2.00mm)
Termination Solder	Mounting Type	Through Hole
	Termination	Solder
Fastening Type Push-Pull	Fastening Type	Push-Pull
Contact Finish - Mating Gold	Contact Finish - Mating	Gold
Contact Finish Thickness - Mating 20µin (0.51µm)	Contact Finish Thickness - Mating	20μin (0.51μm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.250" (6.35mm)	Insulation Height	0.250" (6.35mm)
Contact Length - Post 0.094" (2.40mm)	Contact Length - Post	0.094" (2.40mm)
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### **NPRN234EFCN-RC Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### NPRN234EFCN-RC Payment Methods



















## NPRN234EFCN-RC Shipping Methods













If you have any question about NPRN234EFCN-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com