

NPTC292KFMS-RC

NPTC292KFMS-RC Information



For Reference Only

Part Number NPTC292KFMS-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN FEMALE 58POS DL .1" TIN SMD

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NPTC292KFMS-RC Specifications

Manufacturer Part Number NPTC292KFMS-RC Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Manufacturer Part Number	NPTC292KFMS-RC
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions S Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Coperating Temperature -40°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Category	Connectors, Interconnects
Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions58Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions58Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Series	-
StyleBoard to BoardNumber of Positions58Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Connector Type	Header
Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Number of Positions	58
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post Operating Temperature -40°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.299" (7.60mm)$ Contact Length - Post-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Tin
Insulation Height $0.299" (7.60mm)$ Contact Length - Post - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post - $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.299" (7.60mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

NPTC292KFMS-RC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NPTC292KFMS-RC Payment Methods

































If you have any question about NPTC292KFMS-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com