

# NPTC322KFMP-RC

### NPTC322KFMP-RC Information

Heisener.com

For Reference Only

Part Number NPTC322KFMP-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** CONN HEADER .100" 64POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **NPTC322KFMP-RC Specifications**

Manufacturer Part Number         NPTC322KFMP-RC           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         64           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         -           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.299" (7.60mm)           Contact Length - Post         -           Operating Temperature         -40°C ~ 125°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         64           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.299" (7.60mm)           Contact Length - Post         -           Operating Temperature         -40°C ~ 125°C	Manufacturer Part Number	NPTC322KFMP-RC
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 64 Number of Positions Loaded Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post Contact Length - Post Contact Temperature  -40°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         64           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.299" (7.60mm)           Contact Length - Post         -           Operating Temperature         -40°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Connector Type         Header           Contact Type         Female Socket           Style         Board to Board           Number of Positions         64           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Surface Mount           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.299" (7.60mm)           Contact Length - Post         -           Operating Temperature         -40°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Series	-
StyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Connector Type	Header
Number of Positions 64  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Surface Mount  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.299" (7.60mm)  Contact Length - Post -  Operating Temperature -40°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Style	Board to Board
Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Surface Mount  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.299" (7.60mm)  Contact Length - Post -  Operating Temperature -40°C ~ 125°C	Number of Positions	64
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.299" (7.60mm)  Contact Length - Post -  Operating Temperature -40°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post Operating Temperature -40°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm)  Contact Length - Post - Operating Temperature -40°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.299" (7.60mm)$ Contact Length - Post-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Tin
Insulation Height $0.299" (7.60mm)$ Contact Length - Post -  Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post - $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.299" (7.60mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide
	Report errors?

#### **NPTC322KFMP-RC Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## NPTC322KFMP-RC Payment Methods

































If you have any question about NPTC322KFMP-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com