

**NRS5020T100MMGJV Information**


For Reference Only

**Part Number** [NRS5020T100MMGJV](#)  
**Manufacturer** Taiyo Yuden  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 10UH 1.45A 144 MOHM  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**NRS5020T100MMGJV Specifications**

Manufacturer Part Number	<a href="#">NRS5020T100MMGJV</a>
Manufacturer	Taiyo Yuden
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	NRS
Type	Wirewound
Material - Core	Ferrite
Inductance	10µH
Tolerance	±20%
Current Rating	1.45A
Current - Saturation	1.3A
Shielding	Shielded
DC Resistance (DCR)	144 mOhm Max
Q @ Freq	-
Frequency - Self Resonant	24MHz
Ratings	AEC-Q200
Operating Temperature	-40°C ~ 125°C
Frequency - Test	100kHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	5020
Size / Dimension	0.193" L x 0.193" W (4.90mm x 4.90mm)

Height - Seated (Max)

0.079" (2.00mm)

[Report errors?](#)

## NRS5020T100MMGJV Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## NRS5020T100MMGJV Payment Methods



## NRS5020T100MMGJV Shipping Methods



If you have any question about NRS5020T100MMGJV, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)