


NRVUD340T4G-VF01

NRVUD340T4G-VF01 Information



For Reference Only

Part Number NRVUD340T4G-VF01
Manufacturer ON Semiconductor

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

DescriptionDIODE GEN PURP 400V 3A DPAK**Package**TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NRVUD340T4G-VF01 Specifications

Manufacturer Part NumberNRVUD340T4G-VF01ManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C		
Category Discrete Semiconductor Products Diodes - Rectifiers - Single Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series SWITCHMODE? Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.15V @ 3A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 5µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package DPAK-3 Operating Temperature - Junction	Manufacturer Part Number	NRVUD340T4G-VF01
Diodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Manufacturer	ON Semiconductor
PackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 1.15V @ 3A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 5μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package Operating Temperature - Junction 400V 1.15V @ 3A Fast Recovery =< 500ns, > 200mA (Io) Suns (Io) 50ns Current - Reverse Leakage @ Vr 5μA @ 400V - Table (Io) 50ns Current - Reverse Leakage @ Vr 5μA @ 400V - Table (Io) 50ns 50ns 50ns 50ns 60ns 60n	Series	SWITCHMODE?
Current - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 5μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package Operating Temperature - Junction 1.15V @ 3A 1.15V	Voltage - DC Reverse (Vr) (Max)	400V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Current - Average Rectified (Io)	3A
Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.15V @ 3A
Current - Reverse Leakage @ Vr	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package DPAK-3 Operating Temperature - Junction -55°C ~ 175°C	Reverse Recovery Time (trr)	50ns
Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package DPAK-3 Operating Temperature - Junction -55°C ~ 175°C	Current - Reverse Leakage @ Vr	5μA @ 400V
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package DPAK-3 Operating Temperature - Junction -55°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device Package DPAK-3 Operating Temperature - Junction $-55^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 175°C	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
	Supplier Device Package	DPAK-3
Report errors?	Operating Temperature - Junction	-55°C ~ 175°C
		Report errors?

NRVUD340T4G-VF01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NRVUD340T4G-VF01 Payment Methods



















NRVUD340T4G-VF01 Shipping Methods













If you have any question about NRVUD340T4G-VF01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com