

NSCDANN030PAUNV

NSCDANN030PAUNV Information



For Reference Only

Part Number NSCDANN030PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRESS ABSOLUTE 30PSI**Package**8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSCDANN030PAUNV Specifications

Manufacturer Part NumberNSCDANN030PAUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? NSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 74 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top Port			
CategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? NSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 74 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top Port	Manufacturer Part Number	NSCDANN030PAUNV	
Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? NSC Pressure Type Absolute Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 74 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? NSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 74 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top Port	Category	Sensors, Transducers	
Series TruStability? NSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 74 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port		Pressure Sensors, Transducers	
Pressure Type 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output Output Wheatstone Bridge Output Style ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Package	8-DIP (0.524", 13.30mm), Top Port	
Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 74 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Series	TruStability? NSC	
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 74 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8\text{-DIP } (0.524\text{"}, 13.30\text{mm}), \text{Top Port}$	Pressure Type	Absolute	
Output $0 \text{ mV} \sim 74 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.19'' (4.93 \text{mm}) \text{ Tube}$ Port Style $Barbed$ Features - Termination Style $PC Pin$ Maximum Pressure $60 PSI (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-DIP (0.524'', 13.30 \text{mm}), Top Port$	Operating Pressure	30 PSI (206.84 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male - 0.19" (4.93 mm) Tube}}$ Port Style Barbed Features - Termination Style PC Pin Maximum Pressure $60 \text{ PSI (413.69 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8\text{-DIP (0.524", 13.30 mm), Top Port}$	Output Type	Wheatstone Bridge	
Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male - 0.19" (4.93 \text{mm}) Tube}$ Port Style Barbed Features $-$ Termination Style PC Pin Maximum Pressure $60 \text{ PSI (413.69 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP (0.524", 13.30 \text{mm}), Top Port}$	Output	$0 \text{ mV} \sim 74 \text{ mV } (5\text{V})$	
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Accuracy	±0.25%	
Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Voltage - Supply	1.5 V ~ 12 V	
Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C \sim 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Port Size	Male - 0.19" (4.93mm) Tube	
Termination Style PC Pin Maximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8\text{-DIP } (0.524^{\circ}, 13.30 \text{mm}), \text{Top Port}$	Port Style	Barbed	
Maximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case8-DIP $(0.524^{\circ}, 13.30 \text{mm})$, Top Port	Features	-	
Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port	Termination Style	PC Pin	
Package / Case 8-DIP (0.524", 13.30mm), Top Port	Maximum Pressure	60 PSI (413.69 kPa)	
	Operating Temperature	-40°C ~ 85°C	
	Package / Case	8-DIP (0.524", 13.30mm), Top Port	
Supplier Device Package 8-DIP	Supplier Device Package	8-DIP	
Report errors?		Report e	errors?

NSCDANN030PAUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSCDANN030PAUNV Payment Methods



















NSCDANN030PAUNV Shipping Methods













If you have any question about NSCDANN030PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com