

## NSCDANN060PGUNV

### **NSCDANN060PGUNV Information**



For Reference Only

Part Number NSCDANN060PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRES 60PSI GAUG 12V DIP **Package** 8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **NSCDANN060PGUNV Specifications**

Manufacturer Part Number       NSCDANN060PGUNV         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       8-DIP (0.524", 13.30mm), Top Port         Series       TruStability? NSC         Pressure Type       Vented Gauge         Operating Pressure       60 PSI (413.69 kPa)         Output Type       Wheatstone Bridge         Output       0 mV ~ 103.5 mV (5V)         Accuracy       ±0.25%         Voltage - Supply       1.5 V ~ 12 V         Port Size       Male - 0.19" (4.93mm) Tube         Port Style       Barbed         Features       -         Termination Style       PC Pin         Maximum Pressure       120 PSI (827.37 kPa)         Operating Temperature       -40°C ~ 85°C         Package / Case       8-DIP (0.524", 13.30mm), Top Port         Supplier Device Package       8-DIP		
CategorySensors, TransducersPressure Sensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Manufacturer Part Number	NSCDANN060PGUNV
Package         8-DIP (0.524", 13.30mm), Top Port           Series         TruStability? NSC           Pressure Type         Vented Gauge           Operating Pressure         60 PSI (413.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 103.5 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.5 V ~ 12 V           Port Size         Male - 0.19" (4.93mm) Tube           Port Style         Barbed           Features         -           Termination Style         PC Pin           Maximum Pressure         120 PSI (827.37 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         8-DIP (0.524", 13.30mm), Top Port           Supplier Device Package         8-DIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         8-DIP (0.524", 13.30mm), Top Port           Series         TruStability? NSC           Pressure Type         Vented Gauge           Operating Pressure         60 PSI (413.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 103.5 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.5 V ~ 12 V           Port Size         Male - 0.19" (4.93mm) Tube           Port Style         Barbed           Features         -           Termination Style         PC Pin           Maximum Pressure         120 PSI (827.37 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         8-DIP (0.524", 13.30mm), Top Port           Supplier Device Package         8-DIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Package	8-DIP (0.524", 13.30mm), Top Port
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 103.5 mV (5V) Accuracy ±0.25% Voltage - Supply I.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package 8-DIP  60 PSI (413.69 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge 40.25%  PUP (4.93mm) Tube PC Pin PC Pin PC Pin PC Pin PC Pin PC PSI (827.37 kPa) PC PSI (827.37 kPa) POPORTING TEMPERATURE PHONE SUPPLIES	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 103.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.19$ " ( $4.93\text{mm}$ ) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524^{\circ}, 13.30\text{mm}), \text{Top Port}$ Supplier Device Package $8-\text{DIP}$	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 103.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.19'' (4.93\text{mm}) \text{ Tube}$ Port Style $Barbed$ Features -  Termination Style $PC Pin$ Maximum Pressure $120 PSI (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-DIP (0.524'', 13.30\text{mm}), Top Port$ Supplier Device Package $8-DIP$	Operating Pressure	60 PSI (413.69 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.19$ " ( $4.93\text{mm}$ ) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524^{"}, 13.30\text{mm}), \text{Top Port}$ Supplier Device Package $8-\text{DIP}$	Output Type	Wheatstone Bridge
Voltage - Supply  1.5 V ~ 12 V  Port Size  Male - 0.19" (4.93mm) Tube  Port Style  Barbed  Features  - Termination Style  PC Pin  Maximum Pressure  120 PSI (827.37 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package	Output	0 mV ~ 103.5 mV (5V)
Port Size Male - 0.19" (4.93mm) Tube  Port Style Barbed  Features -  Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Accuracy	±0.25%
Port Style Barbed  Features -  Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Port Size	Male - 0.19" (4.93mm) Tube
Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Port Style	Barbed
Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Features	-
Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Top Port  Supplier Device Package 8-DIP	Termination Style	PC Pin
Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Maximum Pressure	120 PSI (827.37 kPa)
Supplier Device Package 8-DIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	8-DIP (0.524", 13.30mm), Top Port
Report errors?	Supplier Device Package	8-DIP
		Report errors?

### **NSCDANN060PGUNV Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **NSCDANN060PGUNV Payment Methods**



















# NSCDANN060PGUNV Shipping Methods













If you have any question about NSCDANN060PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com