

NSCDANN060PGUNV

NSCDANN060PGUNV Information



For Reference Only

Part Number NSCDANN060PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 60PSI GAUG 12V DIP **Package** 8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSCDANN060PGUNV Specifications

Manufacturer Part Number NSCDANN060PGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 103.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP		
CategorySensors, TransducersPressure Sensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Manufacturer Part Number	NSCDANN060PGUNV
Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 103.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 103.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 103.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Package	8-DIP (0.524", 13.30mm), Top Port
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 103.5 mV (5V) Accuracy ±0.25% Voltage - Supply I.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package 8-DIP 60 PSI (413.69 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge 40.25% PUP (4.93mm) Tube PC Pin PC Pin PC Pin PC Pin PC Pin PC PSI (827.37 kPa) PC PSI (827.37 kPa) POPORTING TEMPERATURE PHONE SUPPLIES	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 103.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524^{\circ}, 13.30\text{mm}), \text{Top Port}$ Supplier Device Package $8-\text{DIP}$	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 103.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.19'' (4.93\text{mm}) \text{ Tube}$ Port Style $Barbed$ Features - Termination Style $PC Pin$ Maximum Pressure $120 PSI (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-DIP (0.524'', 13.30\text{mm}), Top Port$ Supplier Device Package $8-DIP$	Operating Pressure	60 PSI (413.69 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524^{"}, 13.30\text{mm}), \text{Top Port}$ Supplier Device Package $8-\text{DIP}$	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Output	0 mV ~ 103.5 mV (5V)
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Accuracy	±0.25%
Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Port Size	Male - 0.19" (4.93mm) Tube
Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Port Style	Barbed
Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Termination Style	PC Pin
Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Maximum Pressure	120 PSI (827.37 kPa)
Supplier Device Package 8-DIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	8-DIP (0.524", 13.30mm), Top Port
Report errors?	Supplier Device Package	8-DIP
		Report errors?

NSCDANN060PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSCDANN060PGUNV Payment Methods



















NSCDANN060PGUNV Shipping Methods













If you have any question about NSCDANN060PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com